

# Contact Sheet



## Europe

 **Austria**  
Tel: + 43 4212 6400  
Sparex Austria  
Muraunberger Str  
Hurzendorf 9300

 **Belgium / Lux**  
Tel: + 32 58235140  
Sparex Belgium Bvba  
Toevluchtweg 9  
B- 8620 Nieuwpoort

 **Denmark**  
Tel: + 45 647 22287  
Sparex Denmark  
Sparex Limited ApS  
Messevej 1  
9600 Aars

 **France**  
Tel: +33 2987 89234  
Sparex S.A.R.L.  
Zae De Ty Douar  
Commana 29450

 **Germany**  
Tel: + 49 4282 93100  
Sparex Germany  
Hansestrasse 03  
Sittensen 27419

 **Ireland**  
Tel: +353 51 855592  
Sparex (Tractor Accessories) Ltd  
Grannagh  
Waterford  
Ireland

 **Italy**  
Tel: + 43 4212 6400  
Sparex Austria  
Muraunberger Str  
Hurzendorf 9300

 **Netherlands**  
Tel: + 31 235 841 020  
Sparex Holland BV  
Luzernestraat 19N  
2153 GM Nieuw-Vennep

 **Poland**  
Tel: +48 61 816 19 37  
61-168 ul. Rataje 164, Poznań

 **Portugal**  
Tel: +351 261 311107  
Sparex Portugal, Importação  
e Comércio de Peças,Lda.  
Lugar da Espera 2565-716 Runa.

 **Spain**  
Tel: + 349 451 33524  
Sparex Agrirepuestos,S.L. C/Jose Maria  
Iparraguirre  
No.15 B  
01006 Vitoria-Gasteiz (Alava)

 **UK**  
Tel: +44 1392 441338  
Sparex Limited  
Exeter Airport Devon  
Exeter EX5 2LJ

## North America

 **Canada**  
Tel: + 905 786 277  
Sparex Canada Highway  
No. 2 On Newcastle L1b 119

 **USA**  
Tel: + 1 330 562 8150  
Sparex US  
PO Box 510  
Aurora, OH 44202

## Africa

 **South Africa**  
Cape - Tel: +27 00 21 887 3575  
KZN - Tel: + 27 31 573 1240  
Cape branch  
35 George Blake St,  
Plankenburg  
Stellenbosch 7600  
KZN branch  
59 Marseilles crescent  
Briardene  
Durban 4001

## Australasia

 **Australia**  
Tel: + 61 298 205 777  
Sparex Australia Pty Ltd  
81-83 Strzelecki Avenue,  
Sunshine West, VIC 3020

 **New Zealand**  
Tel: + 64 9634 4121  
4 Princes Street Onehunga,  
Auckland 1345

## Sparex Export Markets

 **Export**  
Tel: +44 1392 441314  
Sparex Limited  
Exeter Airport  
Devon Exeter EX5 2LJ



# MATERIAL SAFETY DATA SHEET

## SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** LOCTITE 7471 PRIMER (AEROSOL)

**Proper Shipping Name:** AEROSOLS

**Product Code(s):** 1401912

**Part Number(s):** 21356 (127 gram)

**Use:** Used to increase the cure rate of LOCTITE anaerobic sealants, especially at low temperatures.

**Supplier:** HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996  
ADHESIVE TECHNOLOGIES  
135-141 Canterbury Road, Kilsyth, Victoria, 3137. Tel:(03) 9724 6444  
24 HOUR EMERGENCY CONTACT NUMBER Tel:(03) 9724 6556

## SECTION 2. HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of ASCC. This material has been classified as Irritant (Xi).

### Risk phrase(s):

R11 Highly flammable.  
R36 Irritating to eyes.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

### Safety phrase(s):

S16 Keep away from sources of ignition.  
S23 Do not breathe vapour/spray.  
S24/25 Avoid contact with skin and eyes.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S39 Wear eye/face protection.  
S47 Keep at temperature not exceeding 50° C  
S51 Use only in well ventilated areas.

### DANGEROUS GOODS INFORMATION:

Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Class: 2.1 - Flammable gas

**SUSDP POISON SCHEDULE:** None allocated

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION
Acetone	[67-64-1]	30-60%
Isopropanol	[67-63-0]	< 10%
Benzothiazole derivative		< 1%
N,N-Dialkyltoluidine		< 2%
Hydrocarbon propellant		10-30% w/w

**DATE OF MSDS:** 01.02.10  
Page 1 of 4

**REVISION OF:** 23.05.08  
PROPRIETARY PRODUCT:

**IDH NO:** -  
LOCTITE 7471 PRIMER (AEROSOL)



## MATERIAL SAFETY DATA SHEET

### SECTION 4. FIRST AID MEASURES

**Ingestion:** If swallowed, **do not induce** vomiting. For advice, contact a Poisons Information Centre (Phone 13 11 26) or a doctor.

**Skin:** Remove contaminated clothing and wash affected areas with plenty of water. If irritation occurs, seek medical attention.

**Eyes:** Hold eyes open and flush with water. If irritation occurs, seek medical attention.

**Inhalation:** If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor as soon as possible.

**Advice to doctor:** Treat symptomatically.

**First Aid facilities:** Eye wash and washroom facilities

### SECTION 5. FIRE FIGHTING MEASURES

**Suitable extinguishing media:** Carbon dioxide, foam, dry chemical, water fog.

**Hazards from combustion products:** Under fire conditions, it will produce carbon monoxide and irritating fumes.

**Precautions for fire fighters and special protective equipment:** Heating aerosol containers may cause an explosion. Evacuate unprotected personnel from hazardous area. Fire-fighters should wear full protective clothing and self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Isolate all potential sources of ignition. Wear protective gloves and chemical goggles. For small spills, wipe up with a cloth. For large spills, collect spillage with inert absorbent materials (e.g. sand, earth, vermiculite) and transfer to sealable containers suitable for storing spilled material. Flush areas in contact with spilled material with adequate water to render the area safe for human contact. Do not allow product to enter waterways. Dispose of residues in waste disposal area in accordance with relevant State and Federal requirements.

### SECTION 7. HANDLING AND STORAGE

**Safe Handling:** Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Use with adequate ventilation. Wear butyl rubber gloves<sup>1</sup> and chemical splash goggles. Keep away from strong heat sources and naked flames.

**Storage:** Store indoors in a cool, dry, well ventilated area. Keep containers sealed when not in use. Protect from physical damage. This container is pressurised. Protect from sunlight and do not expose to temperatures exceeding 50° C. Store according to relevant State Dangerous Goods Storage Requirements.

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**National exposure standards:** TWA : 400 ppm (983 mg/m<sup>3</sup>) as isopropanol  
500 ppm (1185 mg/m<sup>3</sup>) as acetone  
STEL: 500 ppm (1230 mg/m<sup>3</sup>) as isopropanol  
1000 ppm (2375 mg/m<sup>3</sup>) as acetone

**Engineering controls:** A local mechanical exhaust system is required where vapour or mist is being generated.



## MATERIAL SAFETY DATA SHEET

**Personal protective equipment:** Avoid contact with skin and eyes. Wear overalls, butyl rubber gloves and chemical splash goggles. Use with adequate ventilation. If inhalation risk exists, wear an organic vapour respirator complying with the requirements of AS 1715 and AS 1716.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical data:**

Appearance: Yellow liquid  
Solubility: Soluble in water  
Flash Point (TCC): -17°C approximately  
Specific gravity: 0.79-0.80 @ 20°C

### SECTION 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under normal conditions of temperature and pressure.

**Conditions to avoid:** Heat, naked flames, sparks.

**Incompatible materials:** Keep away from oxidising agents and acids.

**Hazardous decomposition products:** When heated to decomposition, it will emit carbon monoxide and irritating fumes.

**Hazardous reactions:** Product will not polymerise.

### SECTION 11. TOXICOLOGICAL INFORMATION

**HEALTH EFFECTS:**

**Acute:**

**Ingestion:** If swallowed, may cause irritation to the mouth, throat and digestive tract. Systemic effects may include nausea, vomiting, abdominal pain, metabolic changes and harmful effects to the liver and kidneys.

**Skin:** Contact with skin may result in mild irritation. This product can be absorbed through the skin.

**Eyes:** Liquid contact with the eyes can cause irritation.

**Inhalation:** Inhalation of vapour may cause respiratory irritation, headache, dizziness and drowsiness.

**Chronic:** Repeated or prolonged skin contact may cause defatting of the skin and lead to transient dermatitis.

**Toxicity information:** Oral LD<sub>50</sub> (rat) : 5045 mg/kg as isopropanol  
Oral TDLo (man) : 2857 mg/kg as acetone

### SECTION 12. ECOLOGICAL INFORMATION

Avoid contaminating watercourse and soil. No ecological data is available for this product. Acetone is readily biodegradable.

### SECTION 13. DISPOSAL CONSIDERATIONS

Keep unwanted product in sealed containers for disposal via chemical waste collections. Do not puncture or incinerate containers, even after use. Empty containers should be disposed of at approved land waste site.



## MATERIAL SAFETY DATA SHEET

### SECTION 14. TRANSPORT INFORMATION

UN Number: 1950  
Proper Shipping Name: AEROSOLS  
Class: 2.1  
Packing Group: -  
Hazchem code: -  
Emergency Information: Dangerous Goods-Initial Emergency Response Guide (SAA/SNZ HB 76)  
Guide 49 or EPG 2D1

### SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated

### SECTION 16. OTHER INFORMATION

#### Abbreviations/acronyms:

ASCC - Australian Safety and Compensation Council  
SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons  
TWA - Time-weighted average

#### Reference(s):

1. Quick Selection Guide to Chemical Protective Clothing, Fourth Edition, 2003: Forsberg and Mansdorf, Wiley-Interscience.

#### DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.