Contact Sheet



Europe



Austria

Tel: +43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



France

Tel: +33 2987 89234 Sparex S.A.R.L. Zae De Ty Douar Commana 29450





Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Germany

Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Spain

Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)





Denmark

Tel: + 45 647 22287 Sparex Denmark Sparex Limited ApS Messevej 1 9600 Aars





Ireland

Tel: +353 51 855592 Sparex (Tractor Accessories) Ltd Grannagh Waterford Ireland



Poland

Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Tel: +44 1392 441338 Sparex Limited **Exeter Airport Devon** Exeter EX5 2LJ

North America





Canada

Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119



USA

Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202

Africa



South Africa

Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240

Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Australasia



Australia

Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345

Sparex Export Markets



Export

Tel: +44 1392 441314 Sparex Limited **Exeter Airport** Devon Exeter EX5 2LJ



SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: LOCTITE 596 SUPERFLEX RED HIGH TEMP RTV SEALANT

Product-Code: 198817

Intended use: Silicone sealant

Supplier:

HENKEL AUSTRALIA PTY. LIMITED ADHESIVE TECHNOLOGIES 135-141 Canterbury Road 3137 Kilsyth, Victoria

Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER 03 9724 6556

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of ASCC.

Classification of material Xi - Irritant

Risk phrases:

R36/38 Irritating to eyes and skin.

Safety phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S46 If swallowed, seek medical advice immediately and show this container or label.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Signal word:

HÄZARDOUS

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Methylsilanetriyl triacetate	4253-34-3	1 - 5 %
Triacetoxyethylsilane	17689-77-9	1 - 5 %

Revision: 14.04.2011

Page 1 of 5 LOCTITE 596 SUPERFLEX RED HIGH TEMP RTV SEALANT



SECTION 4. FIRST AID MEASURES

Ingestion: Do not induce vomiting.

Seek medical advice.

Skin: Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide, foam, powder

Fine water spray

Decomposition products in case of

fire:

carbon oxides. Silica fume

Formaldehyde

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions and

emergency procedures:

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Environmental precautions: Do not let product enter drains.

Clean-up methods: Scrape up as much material as possible.

Ensure adequate ventilation.

Store in a partly filled, closed container until disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation.

Conditions for safe storage: Store in a cool, well-ventilated place.

Never allow product to get in contact with water during storage

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards:

Revision: 14.04.2011

Page 2 of 5 LOCTITE 596 SUPERFLEX RED HIGH TEMP RTV SEALANT



None

Engineering controls: Use only with adequate ventilation.

Eye protection: Wear protective glasses.

Skin protection:

The use of chemical resistant gloves such as Nitrile are recommended.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: Use only in well-ventilated areas.

If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: red

paste
Odor: paste

Specific gravity: 1.01

Flash point: > 93 °C (> 199.4 °F)

Vapor pressure: 13 mbar
Density: 1.01 g/cm3

Solubility: Solvent: Water, Not soluble. Polymerizes in presence of water.

Solvent: Acetone, Not determined

VOC content 3.08 %

(2004/42/EC)

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid: Stable under normal conditions of storage and use.

Incompatible materials: Acids.

Bases.

Oxidizing agents.

Polymerises in presence of water.

Hazardous decomposition

products:

Acetic acid is liberated slowly upon contact with moisture.

At higher temperatures (>150C) may release formaldehyde (traces).

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Ingestion: Not expected to be harmful by ingestion.

Ingestion of large amounts may produce gastrointestinal disturbances including irritation,

nausea, and diarrhea.

Skin: May cause skin irritation.

Revision: 14.04.2011

Page 3 of 5 LOCTITE 596 SUPERFLEX RED HIGH TEMP RTV SEALANT



Eyes: Vapors may irritate eyes. Contact with eyes will cause irritation.

Inhalation: Acetic acid produced during cure may irritate eyes, nose and throat.

When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the

OSHA permissible limit.

Chronic effects: No chronic health effects are expected from the intended use of these products or from

foreseeable handling of them in the workplace.

SECTION 12. ECOLOGICAL INFORMATION

General ecological information: Cured Loctite products are typical polymers and do not pose any immediate

environmental hazards.

In the cured state contribution of this product to Environmental Hazards is

insignificant in comparison to articles in which it is used.

Precautions required with respect to Environmental Hazards of articles in which

this product is used should be considered.

Ecotoxicity: Do not empty into drains / surface water / ground water.

Mobility: Cured adhesives are immobile.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal of product: Follow all local, state, federal and provincial regulations for disposal.

Cured rubber can be incinerated or landfilled following EPA and local regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

SECTION 15. REGULATORY INFORMATION

SUSDP Poisons Schedule: None

AICS: All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICS).

Revision: 14.04.2011

Page 4 of 5 LOCTITE 596 SUPERFLEX RED HIGH TEMP RTV SEALANT



SECTION 16. OTHER INFORMATION

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

ASCC - Australian Safety and Compensation Council

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

Date of previous issue: 05.07.2006

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material. The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

Revision: 14.04.2011

Page 5 of 5 LOCTITE 596 SUPERFLEX RED HIGH TEMP RTV SEALANT