

Contact Sheet



Europe

 **Austria**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Belgium / Lux**
Tel: + 32 58235140
Sparex Belgium Bvba
Toevluchtweg 9
B- 8620 Nieuwpoort

 **Denmark**
Tel: + 45 647 22287
Sparex Denmark
Sparex Limited ApS
Messevej 1
9600 Aars

 **France**
Tel: +33 2987 89234
Sparex S.A.R.L.
Zae De Ty Douar
Commana 29450

 **Germany**
Tel: + 49 4282 93100
Sparex Germany
Hansestrasse 03
Sittensen 27419

 **Ireland**
Tel: +353 51 855592
Sparex (Tractor Accessories) Ltd
Grannagh
Waterford
Ireland

 **Italy**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Netherlands**
Tel: + 31 235 841 020
Sparex Holland BV
Luzernstraat 19N
2153 GM Nieuw-Vennep

 **Poland**
Tel: +48 61 816 19 37
61-168 ul. Rataje 164, Poznań

 **Portugal**
Tel: +351 261 311107
Sparex Portugal, Importação
e Comércio de Peças,Lda.
Lugar da Espera 2565-716 Runa.

 **Spain**
Tel: + 349 451 33524
Sparex Agrirepuestos,S.L. C/Jose Maria
Iparraguirre
No.15 B
01006 Vitoria-Gasteiz (Alava)

 **UK**
Tel: +44 1392 441338
Sparex Limited
Exeter Airport Devon
Exeter EX5 2LJ

North America

 **Canada**
Tel: + 905 786 277
Sparex Canada Highway
No. 2 On Newcastle L1b 119

 **USA**
Tel: + 1 330 562 8150
Sparex US
PO Box 510
Aurora, OH 44202

Africa

 **South Africa**
Cape - Tel: +27 00 21 887 3575
KZN - Tel: + 27 31 573 1240
Cape branch
35 George Blake St,
Plankenburg
Stellenbosch 7600
KZN branch
59 Marseilles crescent
Briardene
Durban 4001

Australasia

 **Australia**
Tel: + 61 298 205 777
Sparex Australia Pty Ltd
81-83 Strzelecki Avenue,
Sunshine West, VIC 3020

 **New Zealand**
Tel: + 64 9634 4121
4 Princes Street Onehunga,
Auckland 1345

Sparex Export Markets

 **Export**
Tel: +44 1392 441314
Sparex Limited
Exeter Airport
Devon Exeter EX5 2LJ



MATERIAL SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: LOCTITE 401 PRISM® INSTANT ADHESIVE

Proper Shipping Name: AVIATION REGULATED LIQUID, N.O.S. (CONTAINS CYANOACRYLATE ESTER) Note: Applicable for air transport only.

Product Code(s): 265607, 265618, 265620

Part Number(s): 40124-25 (25 ml), 33531 (100 ml), 33532 (500 ml)

Use: Cyanoacrylate adhesive

Supplier: HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996
ADEHSIVE TECHNOLOGIES
135-141 Canterbury Road, Kilsyth, Victoria, 3137. Tel: (03) 9724 6444
24 HOUR EMERGENCY CONTACT NUMBER: Tel: 1800 032 379

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:
Hazardous according to the criteria of Safe Work Australia. This material has been classified as Irritant (Xi).

Risk Phrase(s):
R36/37/38 - Irritating to eyes, respiratory system and skin.

Safety Phrase(s):
S2 Keep out of reach of children.
S23 Do not breathe vapour.
S24/25 - Avoid contact with skin and eyes.
S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S28 - After contact with skin, wash immediately with plenty of soap suds.
S37/39 - Wear suitable gloves and eye/face protection.
S46 - If swallowed, seek medical advice immediately and show this container or label.

DANGEROUS GOODS INFORMATION:
Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Classified as Dangerous Goods for air transport only.

SUSDP POISON SCHEDULE: 5

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION
Ethyl cyanoacrylate	[7085-85-0]	> 60% w/w

SECTION 4. FIRST AID MEASURES

Ingestion: For advice, contact a Poisons Information Centre (Phone 13 11 26) or a doctor. Ensure that breathing passages are not obstructed. The product will polymerise



MATERIAL SAFETY DATA SHEET

immediately in the mouth, making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

Skin: Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking affected area in warm soapy water. Cyanoacrylates give off heat on solidification. In rare cases, a large drop will generate enough heat to cause a burn. Burns should be treated normally after the adhesive has been removed from the skin. If fingers stick together, apply a solvent such as acetone to contact areas, then wash off with water. Do not use solvents near eyes or open wounds.

If lips are accidentally stuck together, apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eyes: If the eye is bonded closed, release eyelashes with warm water by covering with wet pad. Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

Inhalation: Remove affected person to fresh air. For all but the most minor symptoms, arrange for patient to be seen by a doctor.

Advice to doctor: Treat symptomatically.

First Aid facilities: Eye wash.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Dry powder, foam or carbon dioxide.

Hazards from combustion products: Under fire conditions, it may release toxic fumes.

Precautions for fire fighters and special protective equipment: If there is a risk of exposure to products of combustion, fire-fighters should wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Ventilate area. Do not use cloths for mopping up. Polymerise with water and scrape up. For large spills, wear protective gloves, chemical goggles and boots. Contain and collect spillage with inert absorbent materials (e.g. sand, earth, vermiculite). Transfer to sealable containers suitable for storing spilled material. Wash areas in contact with spilled material with adequate warm soapy water to render the area safe for human contact. Note: Residues are not water soluble. Do not allow product to enter drains. Dispose of solid residues in waste disposal area in accordance with relevant State and Federal requirements.

SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Use in a well ventilated area. Handle carefully. This product will bond instantly in the presence of moisture. Avoid contact with fabric or paper as contact with these materials can generate smoke and irritating vapours.

Storage: Store indoors in a cool, dry and well ventilated area. Keep containers sealed when not in use. Store in original containers. Protect from physical damage. For optimum shelf life, store in original containers under refrigerated conditions at 2°C -10°C.

DATE OF ISSUE: 20.08.10 **REVISION OF:** -19.09.05

Page 2 of 4

PRODUCT NAME:

IDH NO: - LOCTITE 401 PRISM® INSTANT ADHESIVE



MATERIAL SAFETY DATA SHEET

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards: TWA: 0.2 ppm (ACGIH) as for ethyl cyanoacrylate.

Engineering controls: None required under normal conditions of use, but if exposure limits are exceeded, use a local mechanical exhaust system.

Personal protective equipment: Avoid contact with skin and eyes. Wear overalls, polyethylene or nitrile rubber gloves and safety glasses with side shields. Do not use PVC, nylon or cotton gloves. Use with adequate ventilation. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance:	Clear, colourless liquid.
Solubility:	Polymerises in the presence of water
Flash point (TCC):	80°C to 93°C
Odour:	Sharp, characteristic
Specific gravity:	1.05 @ 20°C

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions.

Conditions to avoid: Avoid open flames and heat.

Incompatible materials: Keep away from strong oxidising agents.

Hazardous decomposition products: Combustible material. In a fire, it may release toxic fumes.

Other reactions: Exothermic polymerisation will occur in the presence of water, amines, alkalies and alcohols.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Acute:

Ingestion: Cyanoacrylates are considered to have relatively low toxicity. This product will rapidly polymerise in the mouth.

Skin: Irritating to skin. Bonds skin in seconds.

Eyes: Contact with the eyes will cause irritation. This product will bond eyelids. In a dry atmosphere, vapours may irritate the eyes.

Inhalation: Inhalation of vapours can cause respiratory irritation.

Chronic: Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals.

Toxicity information: Oral LD₅₀ (rat) : > 5000 mg/kg as for cyanoacrylates.



MATERIAL SAFETY DATA SHEET

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate waterways or soil.

SECTION 13. DISPOSAL CONSIDERATIONS

Polymerise by adding slowly to water (10:1). Dispose of solid residues at approved land waste site. Containers should be drained and residues be allowed to cure prior to disposal at approved landfill site.

SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Classified as Dangerous Goods for air transport only. The appropriate air transport requirements shall apply.

U.N. Number: 3334
Proper Shipping Name: AVIATION REGULATED LIQUID, N.O.S.(CONTAINS CYANOACRYLATE ESTER)
Class: 9
Packing Group: -
Hazchem Code: -

SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: 5

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

TWA - Time-weighted average.

ACGIH – American Conference of Governmental Industrial Hygienists.

DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.