# **Contact Sheet**



# Europe



Austria

Tel: +43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



France

Tel: +33 2987 89234 Sparex S.A.R.L. Zae De Ty Douar Commana 29450





Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



**Portugal** 

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Germany

Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Spain

Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)





Denmark

Tel: + 45 647 22287 Sparex Denmark Sparex Limited ApS Messevej 1 9600 Aars





Ireland

Tel: +353 51 855592 Sparex (Tractor Accessories) Ltd Grannagh Waterford Ireland



Poland

Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Tel: +44 1392 441338 Sparex Limited **Exeter Airport Devon** Exeter EX5 2LJ

# **North America**





Canada

Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119



USA

Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202

# **Africa**



South Africa

Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240

Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

# Australasia



Australia

Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345

# **Sparex Export Markets**



Export

Tel: +44 1392 441314 Sparex Limited **Exeter Airport** Devon Exeter EX5 2LJ



SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: LOCTITE BLACK MAXX SILICONE

Proper Shipping Name: None allocated

Other Name(s): BLACK MAXX 598 SILICONE

**Product Code(s):** 640172, 287439

**Part Number(s):** 39145 (95 gram), 34250 (95 gram)

**Use:** Silicone sealant.

Supplier: HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996

ADHESIVE TECHNOLOGIES

135-141 Canterbury Road, Kilsyth, Victoria 3137. Tel: (03) 9724 6444 24 HOUR EMERGENCY CONTACT NUMBER Tel: (03) 9724 6556

# SECTION 2. HAZARDS IDENTIFICATION

#### STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of ASCC. This material has been classified as Harmful (Xn) and Irritant (Xi).

#### Risk phrase(s)

R36/38 Irritating to eyes and skin.

R40 Limited evidence of a carcinogenic effect.

R43 May cause sensitisation by skin contact.

#### Safety phrase(s)

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of soap suds.

S37/39 Wear suitable gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

# **DANGEROUS GOODS INFORMATION:**

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

SUSDP POISON SCHEDULE: None allocated

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **INGREDIENTS:**

Limestone 30-60% w/w	CHEMICAL ENTITY	CAS NO.	PROPORTION	
Carbon black [1333-86-4] 1-5% w/w Methyl ethyl ketoxime [96-29-7] 0.1-1% w/w	Silicone resins Carbon black		30-50% w/w 1-5% w/w	

DATE OF ISSUE:02.12.08REVISION OF:11.07.06IDH NO:-Page 1 of 4PRODUCT NAME:LOCTITE BLACK MAXX SILICONE



SECTION 4. FIRST AID MEASURES

**Ingestion:** If swallowed, **do not induce** vomiting. For advice, contact a Poisons Information

Centre (Phone 13 11 26) or a doctor.

**Skin:** Remove contaminated clothing and wash affected areas with plenty of soap and

water. If irritation occurs, seek medical attention.

**Eyes:** Hold eye open and flush with water for at least 15 minutes. If irritation develops,

seek medical attention.

**Inhalation:** If exposed to processing fumes, remove from contaminated area. For all but the

most minor symptoms, arrange for patient to be seen by a doctor.

Advice to doctor: Treat symptomatically.

First Aid facilities: Eye wash and normal washroom facilities.

#### SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide, foam, dry chemical.

**Hazards from combustion products:** Under fire conditions, it will burn. Upon thermal decomposition this product can release carbon monoxide, oxides of nitrogen, acrid fumes and formaldehyde.

**Precautions for fire fighters and special protective equipment:** If there is a risk of exposure to products of combustion, fire-fighters should wear self contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Wear protective gloves, safety glasses and safety boots. Scrape up residues and place in suitable containers for disposal. Mop up areas in contact with spilled material. Dispose of residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

## SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE

CONTROLS/PERSONAL PROTECTION. Spills are tacky. Avoid accidents, clean

up spills immediately.

**Storage:** Store indoors in a cool, dry, well ventilated area. Keep containers sealed when not

in use. Protect from physical damage and sunlight. Keep away from heat sources and open flames. Store at or below 32°C. Do not allow product to come in contact

with water during storage.

# SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards: None established

**Engineering controls:** None required under normal conditions of use.

**Personal protective equipment:** Avoid contact with skin and eyes. Use with adequate ventilation. Wear overalls, impervious gloves and safety glasses with side shields. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.

DATE OF ISSUE:02.12.08REVISION OF:11.07.06IDH NO:-Page 2 of 4PRODUCT NAME:LOCTITE BLACK MAXX SILICONE



#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance: Black paste. Specific gravity: 1.31 @ 20°C

Solubility in water: Polymerises in the presence of water

#### SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Avoid contact with moisture. Avoid heating this product to temperatures greater

than 150°C.

**Incompatible materials:** Keep away from strong oxidising agents, strong acids and strong bases. **Hazardous decomposition products:** Thermal decomposition products can include carbon

monoxide, oxides of nitrogen, acrid fumes and formaldehyde.

Other reactions: Methyl ethyl ketoxime is formed during the curing process.

# SECTION 11. TOXICOLOGICAL INFORMATION

#### **HEALTH EFFECTS:**

Acute:

Ingestion: Ingestion is an unlikely route of exposure. If ingested, symptoms may include

gastrointestinal irritation, nausea and vomiting.

Skin: Contact with the skin may result in irritation, redness or itching. This product may

cause skin sensitisation in susceptible individuals.

Eyes: Contact with the eyes may cause significant irritation.

Inhalation: Vapours may irritate the nasal passages.

**Chronic:** Repeated or prolonged skin contact may lead to dermatitis. During the curing

process, this product will release up to 5% methyl ethyl ketoxime, for which there

is limited evidence of a carcinogenic effect based on animal data.

Other information: When heated to temperatures greater than 150°C in the presence of air, this

product may release formaldehyde vapours. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitiser. Exposure to moisture during

the curing process will release up to 1% methanol.

**Toxicity information:** None available.

#### SECTION 12. ECOLOGICAL INFORMATION

No ecological information is available for this product. Avoid contaminating waterways, drains and soil.

### SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of the cured material and empty containers at an approved land waste site.

#### SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code).

 DATE OF ISSUE:
 02.12.08
 REVISION OF:
 11.07.06
 IDH NO:

 Page 3 of 4
 PRODUCT NAME:
 LOCTITE BLACK MAXX SILICONE



SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated

SECTION 16. OTHER INFORMATION

#### Abbreviations/acronyms:

ASCC - Australian Safety and Compensation Council

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

#### **DISCLAIMER:**

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

 DATE OF ISSUE:
 02.12.08
 REVISION OF:
 11.07.06
 IDH NO:

 Page 4 of 4
 PRODUCT NAME:
 LOCTITE BLACK MAXX SILICONE