

Contact Sheet



Europe

 **Austria**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Belgium / Lux**
Tel: + 32 58235140
Sparex Belgium Bvba
Toevluchtweg 9
B- 8620 Nieuwpoort

 **Denmark**
Tel: + 45 647 22287
Sparex Denmark
Sparex Limited ApS
Messevej 1
9600 Aars

 **France**
Tel: +33 2987 89234
Sparex S.A.R.L.
Zae De Ty Douar
Commana 29450

 **Germany**
Tel: + 49 4282 93100
Sparex Germany
Hansestrasse 03
Sittensen 27419

 **Ireland**
Tel: +353 51 855592
Sparex (Tractor Accessories) Ltd
Grannagh
Waterford
Ireland

 **Italy**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Netherlands**
Tel: + 31 235 841 020
Sparex Holland BV
Luzernstraat 19N
2153 GM Nieuw-Vennep

 **Poland**
Tel: +48 61 816 19 37
61-168 ul. Rataje 164, Poznań

 **Portugal**
Tel: +351 261 311107
Sparex Portugal, Importação
e Comércio de Peças,Lda.
Lugar da Espera 2565-716 Runa.

 **Spain**
Tel: + 349 451 33524
Sparex Agrirepuestos,S.L. C/Jose Maria
Iparraguirre
No.15 B
01006 Vitoria-Gasteiz (Alava)


 **UK**
Tel: +44 1392 441338
Sparex Limited
Exeter Airport Devon
Exeter EX5 2LJ

North America

 **Canada**
Tel: + 905 786 277
Sparex Canada Highway
No. 2 On Newcastle L1b 119

 **USA**
Tel: + 1 330 562 8150
Sparex US
PO Box 510
Aurora, OH 44202

Africa

 **South Africa**
Cape - Tel: +27 00 21 887 3575
KZN - Tel: + 27 31 573 1240
Cape branch
35 George Blake St,
Plankenburg
Stellenbosch 7600
KZN branch
59 Marseilles crescent
Briardene
Durban 4001

Australasia

 **Australia**
Tel: + 61 298 205 777
Sparex Australia Pty Ltd
81-83 Strzelecki Avenue,
Sunshine West, VIC 3020

 **New Zealand**
Tel: + 64 9634 4121
4 Princes Street Onehunga,
Auckland 1345

Sparex Export Markets

 **Export**
Tel: +44 1392 441314
Sparex Limited
Exeter Airport
Devon Exeter EX5 2LJ



MATERIAL SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: LOCTITE AUTOMOTIVE E-POX-E GLUE 5 MINUTE (HARDENER)

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS AMINOETHYLPIPERAZINE AND ALIPHATIC AMINES)

Product code(s): 354942

Part Number(s): EFQ5

Use: Two-part epoxy based adhesive. LOCTITE AUTOMOTIVE E-POX-E GLUE (HARDENER) is used in conjunction with the RESIN.

Supplier: HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996
ADHESIVE TECHNOLOGIES
135-141 Canterbury Road, Kilsyth, Victoria, 3137. Tel: (03) 9724 6444
24 HOUR EMERGENCY CONTACT NUMBER Tel: (03) 9724 6556

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:

Classified as hazardous according to the criteria of ASCC. This material has been classified as Corrosive (C)

Risk Phrase(s):

R34 Causes burns.
R41 Risk of serious eye damage.
R43 May cause sensitisation by skin contact.

Safety Phrase(s):

S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28 After contact with skin, wash immediately with plenty of soap-suds.
S37/39 Wear suitable gloves and eye/face protection.
S46 If swallowed, seek medical advice immediately and show this container or label.

DANGEROUS GOODS INFORMATION:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

SUSDP POISON SCHEDULE: 5

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION
Polymercaptan	[72244-98-5]	> 60% w/w
2,4,6-Tris (dimethylaminomethyl) phenol	[90-72-2]	1-10% w/w
Aminoethylpiperazine	[140-31-8]	1-10% w/w
Aliphatic amine		1-10% w/w
Silica amorphous, fumed	[112945-52-5]	<2% w/w

DATE OF ISSUE: 11.09.08
Page 1 of 4

REVISION OF: 07.07.06
PRODUCT NAME: LOCTITE AUTOMOTIVE E-POX-E GLUE 5 MINUTE (HARDENER)

IDH NO: -



MATERIAL SAFETY DATA SHEET

SECTION 4. FIRST AID MEASURES

- Ingestion:** If swallowed, **do not** induce vomiting. Seek medical attention or contact a Poisons Information Centre (Phone 13 11 26).
- Skin:** Remove contaminated clothing and wash affected areas with plenty of soap and water. If irritation occurs, seek medical attention.
- Eyes:** Hold eyes open and flush with water for at least 15 minutes. Seek medical attention.
- Inhalation:** If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor.
- Advice to doctor:** Treat symptomatically.
- First Aid facilities:** Eye wash and normal washroom facilities

SECTION 5. FIRE FIGHTING MEASURES

- Suitable extinguishing media:** Carbon dioxide, foam, dry chemical, water fog
- Hazards from combustion products:** Combustible liquid. In a fire, it will emit oxides of carbon, oxides of nitrogen and noxious fumes.
- Precautions for fire fighters and special protective equipment:** If there is a risk of exposure to products of combustion, then fire-fighters should wear full protective clothing and self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Wear impervious gloves, chemical goggles and boots. For smaller spills, wipe up with a cloth. For larger spills, contain and collect spillage with inert absorbent materials (e.g. sand, earth, vermiculite) and transfer to sealable containers suitable for storing spilled material. Use a polar organic solvent to clean up areas in contact with spilled material. Do not contaminate waterways. Dispose of residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Wear impervious gloves and chemical splash goggles. Upon mixing hardener with resin, the adhesive will release heat and begin to cure. Do not cut or heat empty containers, as they may contain product residue. If the cured material is cut or dry sanded, wear an approved particulate respirator.

Storage: Store indoors in a cool, dry, well ventilated area. Keep containers sealed when not in use. Protect from physical damage and direct sunlight.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- National exposure standards:** None established
- Engineering controls:** In confined areas, use a local mechanical exhaust system if vapour is being generated.

Personal protective equipment: Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, safety footwear, impervious gloves and chemical splash goggles. Use in a well

DATE OF ISSUE: 11.09.08
Page 2 of 4

REVISION OF: 07.07.06
PRODUCT NAME: LOCTITE AUTOMOTIVE E-POX-E GLUE 5 MINUTE (HARDENER)

IDH NO: -



MATERIAL SAFETY DATA SHEET

ventilated area. In poorly ventilated areas, wear a respirator complying with the requirements of AS 1715 and AS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance: Amber liquid
Specific gravity: 1.04
Solubility: Slightly soluble in water
Flash point: >93°C
Odour: Mercaptan
VOC content: 3.7%

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Avoid heat, ignition sources and flames.

Incompatible materials: Keep away from acids, alkalies and oxidising agents.

Hazardous decomposition products: When heated to decomposition, it will emit oxides of carbon, oxides of nitrogen and noxious fumes.

Hazardous reactions: Exothermic polymerisation will occur with epoxy resins.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Acute:

Ingestion: If swallowed, this product will cause burns to the mouth, throat and digestive tract.

Skin: Contact with the skin can result in burns. This product may cause skin sensitisation in susceptible individuals.

Eyes: Contact with the eyes can cause severe irritation which may result in eye damage.

Inhalation: Inhalation of vapour may cause irritation to the respiratory tract.

Chronic: Repeated skin contact may cause superficial damage to skin tissue.

Toxicity information: Acute Oral LD₅₀ (rat) : 1637 mg/kg as tris (dimethylaminomethyl) phenol.

SECTION 12. ECOLOGICAL INFORMATION

No ecological information is available for this product. Do not contaminate waterways and soil.

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of any unwanted material via chemical waste collections. Empty containers should be recycled or disposed of at approved land waste site.



MATERIAL SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

UN Number: 2735
Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS AMINOETHYLPIPERAZINE AND ALIPHATIC AMINES)
Class: 8
Packing group: II
Hazchem Code: 3X
Emergency Information: Refer to Dangerous Goods- Initial Emergency Response Guide (SAA/SNZ HB 76) or EPG 8A1

SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: 5

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

ASCC - Australian Safety and Compensation Council
SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.