

Contact Sheet



Europe

 **Austria**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Belgium / Lux**
Tel: + 32 58235140
Sparex Belgium Bvba
Toevluchtweg 9
B- 8620 Nieuwpoort

 **Denmark**
Tel: + 45 647 22287
Sparex Denmark
Sparex Limited ApS
Messevej 1
9600 Aars

 **France**
Tel: +33 2987 89234
Sparex S.A.R.L.
Zae De Ty Douar
Commana 29450

 **Germany**
Tel: + 49 4282 93100
Sparex Germany
Hansestrasse 03
Sittensen 27419

 **Ireland**
Tel: +353 51 855592
Sparex (Tractor Accessories) Ltd
Grannagh
Waterford
Ireland

 **Italy**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Netherlands**
Tel: + 31 235 841 020
Sparex Holland BV
Luzernstraat 19N
2153 GM Nieuw-Vennep

 **Poland**
Tel: +48 61 816 19 37
61-168 ul. Rataje 164, Poznań

 **Portugal**
Tel: +351 261 311107
Sparex Portugal, Importação
e Comércio de Peças,Lda.
Lugar da Espera 2565-716 Runa.

 **Spain**
Tel: + 349 451 33524
Sparex Agrirepuestos,S.L. C/Jose Maria
Iparraguirre
No.15 B
01006 Vitoria-Gasteiz (Alava)

 **UK**
Tel: +44 1392 441338
Sparex Limited
Exeter Airport Devon
Exeter EX5 2LJ

North America

 **Canada**
Tel: + 905 786 277
Sparex Canada Highway
No. 2 On Newcastle L1b 119

 **USA**
Tel: + 1 330 562 8150
Sparex US
PO Box 510
Aurora, OH 44202

Africa

 **South Africa**
Cape - Tel: +27 00 21 887 3575
KZN - Tel: + 27 31 573 1240
Cape branch
35 George Blake St,
Plankenburg
Stellenbosch 7600
KZN branch
59 Marseilles crescent
Briardene
Durban 4001

Australasia

 **Australia**
Tel: + 61 298 205 777
Sparex Australia Pty Ltd
81-83 Strzelecki Avenue,
Sunshine West, VIC 3020

 **New Zealand**
Tel: + 64 9634 4121
4 Princes Street Onehunga,
Auckland 1345

Sparex Export Markets

 **Export**
Tel: +44 1392 441314
Sparex Limited
Exeter Airport
Devon Exeter EX5 2LJ



MATERIAL SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: LOCTITE SOLVO-RUST SUPER PENETRATING OIL (AEROSOL)

Proper Shipping Name: AEROSOLS

Product Code: 473164

Part Number: 81252

Use: Lubricant.

Supplier: HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996
ADHESIVE TECHNOLOGIES
135-141 Canterbury Road, Kilsyth, Victoria, 3137 Tel: (03) 9724 6444
24 HOUR EMERGENCY CONTACT NUMBER Tel: (03) 9724 6556

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of ASCC. This material has been classified as Harmful (Xn).

Risk phrase(s):

R65 Harmful: May cause lung damage if swallowed.

Safety phrase(s):

S2 Keep out of reach of children.
S16 Keep away from sources of ignition.
S23 Do not breathe vapour/spray.
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37/39 Wear suitable gloves and eye/face protection.
S47 Keep at temperature not exceeding 50°C
S51 Use only in well ventilated areas.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

DANGEROUS GOODS INFORMATION:

Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Class: 2.1

SUSDP POISON SCHEDULE: None allocated

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION
Naphtha (petroleum) hydrotreated naphthenic	[64742-52-5]	30-60% w/w
Aliphatic naphtha	[64742-88-7]	10-30% w/w
Kerosene	[8008-20-6]	10-30% w/w
Hydrocarbon propellants	[106-97-8] [74-98-6]	30-60% w/w

DATE OF ISSUE: 19.12.06
Page 1 of 4

REVISION OF: -
PRODUCT NAME: LOCTITE SOLVO-RUST SUPER PENETRATING OIL (AEROSOL)

IDH NO: -



MATERIAL SAFETY DATA SHEET

SECTION 4. FIRST AID MEASURES

- Ingestion:** If swallowed, **do not induce** vomiting. For advice, contact a Poisons Information Centre (Phone 13 11 26) or a doctor.
- Skin:** Remove contaminated clothing and wash affected areas with running water. If irritation occurs, seek medical advice.
- Eyes:** Hold eyes open and flush immediately with running water. If irritation occurs, seek medical advice.
- Inhalation:** If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor as soon as possible.
- Advice to doctor:** Treat symptomatically.
- First Aid facilities:** Eye wash and normal washroom facilities.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Foam, carbon dioxide, dry chemical.

Hazardous decomposition products: Under fire conditions, it will produce carbon monoxide and noxious fumes.

Precautions for fire fighters and special protective equipment: This product is flammable. Vapours are heavier than air and may accumulate in low areas or poorly ventilated areas to be ignited at locations distant from the handling site. Heating aerosol containers may cause an explosion. Fire-fighters should wear full protective clothing and self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Isolate all potential sources of ignition. Wear protective gloves, chemical goggles and waterproof boots. Contain and collect spillage with absorbent materials (e.g. sand, earth, vermiculite). Transfer to sealable containers suitable for storing spilled material. Mop up areas in contact with spilled material. Note: Residues are not water soluble. Do not contaminate watercourse. Dispose of residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Wear impervious gloves¹ and chemical splash goggles. Keep away from heat sources and naked flames. Use in a well ventilated area.

Storage: Store indoors in a cool, dry, well ventilated area. Protect from physical damage. This container is pressurised. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not spray on a naked flame or any incandescent material. Store according to relevant State Dangerous Goods Storage Requirements.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards: TWA : 100 ppm as for petroleum solvent (recommended)
800 ppm (1900 mg/m³) as butane.

Engineering controls: In confined areas, a local mechanical exhaust system is required where vapour or mist is being generated.

Personal protective equipment: Avoid contact with skin and eyes. Do not breathe vapour or spray mist. Wear enclosed footwear, neoprene rubber gloves and chemical splash goggles or full face



MATERIAL SAFETY DATA SHEET

shield. Use in a well ventilated area. If inhalation risk exists, wear an organic vapour respirator complying with the requirements of AS 1715 and AS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance:	Off-white to pale yellow liquid
Specific gravity:	0.76 @ 20°C
Odour:	Petroleum
Solubility:	Insoluble in water
Flash point(PMCC):	60°C
VOC content:	49.9%

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Avoid heat sources and open flames.

Incompatible materials: Keep away from oxidising agents.

Hazardous decomposition products: When heated to decomposition, it will emit carbon monoxide and noxious fumes.

Hazardous reactions: Will not polymerise.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Acute:

Ingestion: If swallowed, this product may cause irritation to the mouth, throat and digestive tract. Aspiration of small droplets into the lungs may cause pneumonitis or pulmonary oedema.

Skin: Contact with skin may cause mild irritation.

Eyes: Liquid contact with the eyes may cause irritation.

Inhalation: Inhalation of vapour may cause respiratory irritation, drowsiness and dizziness.

Chronic: Repeated or prolonged skin contact may cause defatting of the skin and lead to dermatitis.

Toxicity information: None available for this preparation.

SECTION 12. ECOLOGICAL INFORMATION

Do not contaminate waterways and soil. No ecological information is available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of this material at a chemical waste site. Do not puncture or incinerate containers, even after use. Empty containers should be disposed of at an approved landfill site.

SECTION 14. TRANSPORT INFORMATION

UN Number:	1950
Proper Shipping Name:	AEROSOLS
Class:	2.1
Packing Group:	-
Hazchem code:	-



MATERIAL SAFETY DATA SHEET

Emergency Information: Refer to Dangerous Goods-Initial Emergency Response Guide (SAA/SNZ HB 76) Guide 49 or EPG 2D1.

SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

ASCC - Australian Safety and Compensation Council

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

TWA - Time-weighted average

References:

1. Quick Selection Guide to Chemical Protective Clothing, Fourth Edition, 2003: Forsberg and Mansdorf, Wiley-Interscience.

DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.