Contact Sheet



Europe

Austria Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Canada Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119





Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345





Poland Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Africa



Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Sparex Export Markets

(*) Export

Tel: +44 1392 441314 Sparex Limited Exeter Airport Devon Exeter EX5 2LJ

www.sparex.com



SECTION 1. IDENTI	FICATION OF THE MATERIAL AND SUPPLIER
Product Name:	LOCTITE AUTOMOTIVE SUPER GLUE XTRA
Proper Shipping Name:	AVIATION REGULATED LIQUID, N.O.S. (CYANOACRYLATE ESTER) Note: Applicable for air transport only.
Product Code(s):	161942
Part Number(s):	SGX3 (3g)
Use:	Cyanoacrylate adhesive
Supplier:	HENKEL AUSTRALIA PTY. LIMITEDABN82 001 302 996TECHNOLOGIES135-141 Canterbury Road, Kilsyth, Victoria, 3137.Tel:(03) 9724 644424 HOUR EMERGENCY CONTACT NUMBERTel:(03) 9724 6556

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of ASCC. This material has been classified as Irritant (Xi).

Risk Phrase(s):

R36/37/38 Irritating to eyes, respiratory system and skin.

Safety Phrase(s):

S2 Keep out of reach of children.

S23 Do not breathe vapour.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S28 After contact with skin, wash immediately with plenty of soap suds.

S37/39 Wear suitable gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.

DANGEROUS GOODS INFORMATION:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Classified as Dangerous Goods for air transport only.

SUSDP POISON SCHEDULE: None allocated

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION
Ethyl cyanoacrylate	[7085-85-0]	> 80% w/w

SECTION 4. FIRST AID MEASURES

Ingestion: For advice, contact a Poisons Information Centre (Phone 13 11 26) or a doctor. Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth, making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).



Skin:	Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking affected area in warm soapy water. Cyanoacrylates give off heat on solidification. In rare cases, a large drop will generate enough heat to cause a burn. Burns should be treated normally after the adhesive has been removed from the skin. If fingers stick together, apply a solvent such as acetone to contact areas, then wash off with water. Do not use solvents near eyes or open wounds.
	If lips are accidentally stuck together, apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.
Eyes:	If the eye is bonded closed, release eyelashes with warm water by covering with wet pad. Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.
Inhalation:	Remove affected person to fresh air. For all but the most minor symptoms, arrange for patient to be seen by a doctor.
Advice to doctor:	Treat symptomatically.

First Aid facilities: Eye wash.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Dry powder, foam or carbon dioxide, water fog.

Hazards from combustion products: Under fire conditions, it may release toxic fumes.

Precautions for fire fighters and special protective equipment: If there is a risk of exposure to products of combustion, fire-fighters should wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Ventilate area. Do not use cloths for mopping up. Polymerise with water and scrape up. For large spills, wear protective gloves, chemical goggles and waterproof boots. Collect spillage with inert absorbent materials (e.g. sand, earth, vermiculite) or polymerise with water and scrape up. Transfer to sealable containers suitable for storing spilled material. Do not contaminate watercourse. Dispose of solid residues in waste disposal area in accordance with relevant State and Federal requirements.

SECTION 7. HANDLING AND STORAGE

Safe Handling: Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Use in a well ventilated area. Handle carefully. This product will bond instantly in the presence of moisture.

Storage: Store indoors in a cool, dry and well ventilated area. Keep containers sealed when not in use. Store in original containers. Protect from physical damage. For optimum shelf life, store in original containers under refrigerated conditions at 2°C - 8°C.



SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards: TWA: 0.2 ppm (ACGIH) as for ethyl cyanoacrylate.

Engineering controls: None required under normal conditions of use. In confined areas, a local mechanical exhaust system is recommended.

Personal protective equipment: Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, polyethylene or polypropylene gloves and safety glasses with side shields. Do not use PVC, rubber, nylon or cotton gloves. Use in a well ventilated area. If inhalation risk exists, wear a respirator complying with the requirements of AS 1715 and AS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical data:

Appearance:Clear, colourless liquid.Solubility:Not miscible with water (soluble in acetone)Flash point (PMCC):> 80°COdour:Sharp, characteristicSpecific gravity:1.1 @ 20°C

SECTION 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions.

Conditions to avoid: Avoid open flames and heat. Polymerisation will occur in the presence of moisture.

Incompatible materials: Keep away from strong oxidising agents.

Hazardous decomposition products: Combustible material. In a fire, it may release toxic fumes.

Other reactions: May polymerise if exposed to alkalies, amines, alcohols and peroxides.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Acute: Ingestion:	Cyanoacrylates are considered to have relatively low toxicity. This product will rapidly polymerise in the mouth.	
Skin:	Irritating to skin. Bonds skin in seconds.	
Eyes:	Contact with the eyes will cause irritation. This product will bond eyelids. In a dry atmosphere with less than 50% relative humidity, vapours may irritate the eyes.	
Inhalation:	Inhalation of vapours can cause respiratory irritation.	
Chronic:	Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals.	
Toxicity information: Oral I D_{re} (rat) $\therefore 5000$ mg/kg as for cyanoactylates		

Toxicity information: Oral LD_{50} (rat) : > 5000 mg/kg as for cyanoacrylates.



SECTION 12. ECOLOGICAL INFORMATION

Do not allow product to contaminate waterways or soil. This product is biodegradable.

SECTION 13. DISPOSAL CONSIDERATIONS

Polymerise by adding slowly to water (10:1). Dispose of solid residues at an approved land waste site. Containers should be drained and any residues be allowed to cure prior to disposal at an approved landfill site.

SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Classified as Dangerous Goods for air transport only. The appropriate air transport requirements shall apply.

U.N. Number:	3334
Proper Shipping Name:	AVIATION REGULATED LIQUID, N.O.S. (CYANOACRYLATE ESTER)
Class:	9
Packing Group:	-
Hazchem Code:	-
Packing Group:	-

SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: None allocated

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms:

ASCC - Australian Safety and Compensation Council SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons TWA - Time-weighted average. ACGIH – American Conference of Governmental Industrial Hygienists.

DISCLAIMER:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.