

Contact Sheet



Europe

 **Austria**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Belgium / Lux**
Tel: + 32 58235140
Sparex Belgium Bvba
Toevluchtweg 9
B- 8620 Nieuwpoort

 **Denmark**
Tel: + 45 647 22287
Sparex Denmark
Sparex Limited ApS
Messevej 1
9600 Aars

 **France**
Tel: +33 2987 89234
Sparex S.A.R.L.
Zae De Ty Douar
Commana 29450

 **Germany**
Tel: + 49 4282 93100
Sparex Germany
Hansestrasse 03
Sittensen 27419

 **Ireland**
Tel: +353 51 855592
Sparex (Tractor Accessories) Ltd
Grannagh
Waterford
Ireland

 **Italy**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Netherlands**
Tel: + 31 235 841 020
Sparex Holland BV
Luzernestraat 19N
2153 GM Nieuw-Vennep

 **Poland**
Tel: +48 61 816 19 37
61-168 ul. Rataje 164, Poznań

 **Portugal**
Tel: +351 261 311107
Sparex Portugal, Importação
e Comércio de Peças,Lda.
Lugar da Espera 2565-716 Runa.

 **Spain**
Tel: + 349 451 33524
Sparex Agrirepuestos,S.L. C/Jose Maria
Iparraguirre
No.15 B
01006 Vitoria-Gasteiz (Alava)

 **UK**
Tel: +44 1392 441338
Sparex Limited
Exeter Airport Devon
Exeter EX5 2LJ

North America

 **Canada**
Tel: + 905 786 277
Sparex Canada Highway
No. 2 On Newcastle L1b 119

 **USA**
Tel: + 1 330 562 8150
Sparex US
PO Box 510
Aurora, OH 44202

Africa

 **South Africa**
Cape - Tel: +27 00 21 887 3575
KZN - Tel: + 27 31 573 1240
Cape branch
35 George Blake St,
Plankenburg
Stellenbosch 7600
KZN branch
59 Marseilles crescent
Briardene
Durban 4001

Australasia

 **Australia**
Tel: + 61 298 205 777
Sparex Australia Pty Ltd
81-83 Strzelecki Avenue,
Sunshine West, VIC 3020

 **New Zealand**
Tel: + 64 9634 4121
4 Princes Street Onehunga,
Auckland 1345

Sparex Export Markets

 **Export**
Tel: +44 1392 441314
Sparex Limited
Exeter Airport
Devon Exeter EX5 2LJ



SAFETY DATA SHEET TETROSEAL WAX OIL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name TETROSEAL WAX OIL

Product number TWO500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Underbody coat.

1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

Manufacturer TETROSYL LIMITED
Bury
Lancashire
England
BL9 7NY
0161 764 5981
0161 797 5899
info@tetrosyl.com

1.4. Emergency telephone number

Emergency telephone +44 (0)161 764 5981

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards STOT SE 3 - H336

Environmental hazards Aquatic Chronic 3 - H412

Environmental The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

TETROSEAL WAX OIL

Pictogram



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTRE/doctor if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/ container in accordance with national regulations.
 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.

Contains

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS (<0.1% BENZENE CONTENT)

Detergent labelling

≥ 30% aliphatic hydrocarbons

2.3. Other hazards

Not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C9 - C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	30-<60%
CAS number: —	EC number: 919-857-5
REACH registration number: 01-2119463258-33-XXXX	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304	
PETROLEUM GASES, LIQUEFIED	30-<60%
CAS number: 68476-85-7	EC number: 270-704-2
Classification Flam. Gas 1 - H220	

TETROSEAL WAX OIL

Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Wash skin thoroughly with soap and water. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
Inhalation	May cause an asthma-like shortness of breath. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Drowsiness, dizziness, disorientation, vertigo. Vapours may cause drowsiness and dizziness. Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. Due to the physical nature of this material it is unlikely that swallowing will occur.
Skin contact	Prolonged contact may cause redness, irritation and dry skin. May cause skin irritation/eczema.
Eye contact	Severe irritation, burning and tearing. Vapour, spray or dust may cause chronic eye irritation or eye damage. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Foam, carbon dioxide or dry powder. Water spray. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Extremely flammable. Severe explosion hazard when vapours are exposed to flames. Risk of explosion if heated. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	---

TETROSEAL WAX OIL

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting Risk of re-ignition after fire has been extinguished. Risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up For waste disposal, see Section 13. If leakage cannot be stopped, evacuate area. Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not use in confined spaces without adequate ventilation and/or respirator. Mechanical ventilation or local exhaust ventilation may be required. Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep containers upright. Protect against physical damage and/or friction. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Do not store for long periods. Do not store in large quantities. Store in a cool and well-ventilated place. Keep container dry. Do not store near heat sources or expose to high temperatures.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

TETROSEAL WAX OIL

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits known for ingredient(s).

PETROLEUM GASES, LIQUEFIED

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

Carc

BUTYL GLYCOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³

Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³

Sk

WEL = Workplace Exposure Limit

Carc = Capable of causing cancer and/or heritable genetic damage.

Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

No specific hand protection recommended. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Provide eyewash station. Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Do not smoke in work area. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Opaque liquid. Coloured liquid.
Colour	Light brown.
Odour	Hydrocarbons.
Odour threshold	Not determined. Not determined.
pH	Not determined.
Melting point	Not determined.

TETROSEAL WAX OIL

Initial boiling point and range	Technically not feasible.
Flash point	Technically not feasible.
Evaporation rate	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.800 @ °C
Solubility(ies)	Insoluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	750-850 cP @ 20°C
Oxidising properties	Not determined.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product. Vapours may form explosive mixtures with air.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

TETROSEAL WAX OIL

Reproductive toxicity

Reproductive toxicity - fertility No evidence of reproductive toxicity in animal studies.

Specific target organ toxicity - single exposure

STOT - single exposure Central nervous system depression including narcotic effects such as drowsiness, narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Morphological changes that are potentially reversible but provide clear evidence of marked organ dysfunction.

Target organs Skin

Aspiration hazard

Aspiration hazard Not applicable.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapour may irritate respiratory system/lungs.

Ingestion

Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Eye contact

Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health hazards

This chemical can be hazardous when inhaled and/or touched. This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns. May cause severe internal injury. Vapour from this product may be hazardous by inhalation.

Route of exposure

Inhalation Ingestion. Skin and/or eye contact Skin absorption

Target organs

Skin Central nervous system Eyes Respiratory system, lungs

Medical symptoms

Skin irritation. Irritation of eyes and mucous membranes. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

Medical considerations

Skin disorders and allergies.

SECTION 12: Ecological information

Ecotoxicity

Dangerous for the environment. May cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish

LC₅₀, 96 hours: <30mg/l (White Spirit) mg/l, Fish

Acute toxicity - aquatic invertebrates

EC₅₀, 48 hours: 10 - 22mg/l (White Spirit) mg/l, Daphnia magna

Acute toxicity - aquatic plants

IC₅₀, 72 hours: 4.6 - 10mg/l (White Spirit) mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability

The product is expected to be slowly biodegradable.

12.3. Bioaccumulative potential

TETROSEAL WAX OIL

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

Adsorption/desorption coefficient Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Do not puncture or incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



14.4. Packing group

TETROSEAL WAX OIL

ADR/RID packing group #
 IMDG packing group #
 ICAO packing group #

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
 No.

14.6. Special precautions for user

EmS F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78
 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	EH40/2005 Workplace exposure limits
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Health & Safety Department
Revision date	09/03/2015
Revision	6
Supersedes date	23/06/2014 v5
SDS status	Approved.

TETROSEAL WAX OIL

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.