

Contact Sheet



Europe

 **Austria**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Belgium / Lux**
Tel: + 32 58235140
Sparex Belgium Bvba
Toevluchtweg 9
B- 8620 Nieuwpoort

 **Denmark**
Tel: + 45 647 22287
Sparex Denmark
Sparex Limited ApS
Messevej 1
9600 Aars

 **France**
Tel: +33 2987 89234
Sparex S.A.R.L.
Zae De Ty Douar
Commana 29450

 **Germany**
Tel: + 49 4282 93100
Sparex Germany
Hansestrasse 03
Sittensen 27419

 **Ireland**
Tel: +353 51 855592
Sparex (Tractor Accessories) Ltd
Grannagh
Waterford
Ireland

 **Italy**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Netherlands**
Tel: + 31 235 841 020
Sparex Holland BV
Luzernstraat 19N
2153 GM Nieuw-Vennep

 **Poland**
Tel: +48 61 816 19 37
61-168 ul. Rataje 164, Poznań

 **Portugal**
Tel: +351 261 311107
Sparex Portugal, Importação
e Comércio de Peças,Lda.
Lugar da Espera 2565-716 Runa.

 **Spain**
Tel: + 349 451 33524
Sparex Agrirepuestos,S.L. C/Jose Maria
Iparraguirre
No.15 B
01006 Vitoria-Gasteiz (Alava)

 **UK**
Tel: +44 1392 441338
Sparex Limited
Exeter Airport Devon
Exeter EX5 2LJ

North America

 **Canada**
Tel: + 905 786 277
Sparex Canada Highway
No. 2 On Newcastle L1b 119

 **USA**
Tel: + 1 330 562 8150
Sparex US
PO Box 510
Aurora, OH 44202

Africa

 **South Africa**
Cape - Tel: +27 00 21 887 3575
KZN - Tel: + 27 31 573 1240
Cape branch
35 George Blake St,
Plankenburg
Stellenbosch 7600
KZN branch
59 Marseilles crescent
Briardene
Durban 4001

Australasia

 **Australia**
Tel: + 61 298 205 777
Sparex Australia Pty Ltd
81-83 Strzelecki Avenue,
Sunshine West, VIC 3020

 **New Zealand**
Tel: + 64 9634 4121
4 Princes Street Onehunga,
Auckland 1345

Sparex Export Markets

 **Export**
Tel: +44 1392 441314
Sparex Limited
Exeter Airport
Devon Exeter EX5 2LJ

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

TIP TOP CEMENT SVS VULC

Art.-No.

505 0196, 505 4037, 505 4051, 505 9010, 505 9017, 505 9018, 505 9025, 505 9032, 505 9035, 505 9036, 505 9037, 505 9038, 505 9050, 505 9055, 505 9056, 505 9127, 505 9128, 505 9142, 505 9145, 505 9159, 505 9197, 505 9198, 505 9245, 505 9246, 505 9252, 506 0000, 506 0006, 506 0007, 506 0021, 506 0045, 506 0048, 506 0100, 506 0103, 506 0117, 506 0193, 506 0194, 506 0203, 506 0306, 506 0308, 506 0375, 506 0376, 506 0518, 506 0519, 506 0605, 506 0900, 506 0911, 506 0912, 506 1500, 506 4003, 506 4004, 506 4005, 506 4027, 506 4041, 506 4106, 506 4190, 506 4191, 506 4195, 506 4199, 506 4200, 506 4201, 506 4209, 506 4254, 506 4302, 506 4371, 506 4515, 506 4601, 506 8100, 506 9015, 506 9022, 506 9030, 506 9053, 506 9060, 506 9101, 506 9118, 506 9120, 506 9132, 506 9133, 506 9148, 506 9149, 506 9150, 506 9163, 506 9170, 506 9190, 506 9500, 506 9510, 506 9520, 506 9521, 506 9534, 506 9637, 506 9716, 506 9724, 506 9730, 507 0011, 507 0012, 507 0310, 507 0311, 507 0602, 507 0603, 507 9706, 507 9892, 507 9971, 546 2313, 552 3190, 552 3197, 552 3198, 552 3199, 552 4196, 596 4354, 5042, 5042-10, 5054, 5952, 5952-10, 5098-10, 5097, 5098, 5096, 5106

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

adhesive

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 65
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 100
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Naphtha (petroleum)

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 2 of 10

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.
P501	Dispose of contents/container to waste treatment facility in accordance with local and national regulations .

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.
Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation solved in petroleum spirit

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
64742-49-0	Naphtha (petroleum) (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane)	< 95 %
	921-024-6	649-328-00-1
	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
5459-93-8	N-Cyclohexyl-N-ethylamine	< 2,5 %
	226-733-8	01-2119949285-29
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Aquatic Chronic 3; H226 H311 H332 H302 H314 H412	

Full text of H and EUH statements: see section 16.

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphtha (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 3 of 10

weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
Seek medical treatment immediately.

After contact with skin

Wash off immediately with soap and plenty of water.
Treat subsequently with skin cream.
Consult a doctor if skin irritation persists.

After contact with eyes

If eye irritation persists, consult a specialist.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

After ingestion

Do not induce vomiting.
Attention. Beware, danger of aspiration.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 4 of 10

6.1. Personal precautions, protective equipment and emergency procedures

- In case of vapour formation use respirator.
- Use only explosion-proof equipment.
- Avoid contact with skin, eyes and clothing.
- Ensure adequate ventilation.
- Use personal protective clothing.

6.2. Environmental precautions

- Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
- Shovel into suitable container for disposal.

6.4. Reference to other sections

- Observe protective instructions (see Sections 7 and 8).
- Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Keep container tightly closed.
- Vapours are heavier than air and spread along ground.
- Use only in thoroughly ventilated areas.
- Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

- Keep away from heat and sources of ignition.
- Do not smoke.
- Take precautionary measures against static discharges.
- Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion rules.

Advice on storage compatibility

- Incompatible with oxidizing agents.

Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

- adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

- Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

- Do not inhale vapours.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Treat subsequently with skin cream.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 5 of 10

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Colourless
Odour:	Hydrocarbon-like

Test method

pH-Value: n.d.

Changes in the physical state

Melting point:	< - 50 °C *)
Initial boiling point and boiling range:	> 60 °C
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	- 25 °C DIN EN ISO 3679

Flammability

Solid:	n.a.
Gas:	n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	0,8 vol. % *)
Upper explosion limits:	8,0 vol. % *)
Ignition temperature:	260 °C *)

Auto-ignition temperature

Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n.d.

Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	190 hPa *)
Density (at 20 °C):	0,72 g/cm ³



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 6 of 10

Water solubility: (at 20 °C)	Immiscible
Solubility in other solvents n.d.	
Partition coefficient:	n.d.
Viscosity / dynamic:	2900 - 3500 mPa·s
Viscosity / kinematic: (at 40 °C)	2485 - 2535 mm ² /s
Flow time: (at 23 °C)	> 30 s 3 DIN EN ISO 2431
Vapour density:	n.d.
Evaporation rate:	n.d.
Solvent separation test:	0 %
Solvent content:	> 90 %

9.2. Other information

*) Naphtha (petroleum)

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)
An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.
No toxicological data available.
Naphtha (petroleum)
LD₅₀/oral/rat: > 2000 mg/kg
LD₅₀/dermal/rabbit: > 2000 mg/kg
LC₅₀/inhalation/rat: No data available.

Irritation and corrosivity

Causes serious eye irritation.
Causes skin irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 7 of 10

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum) (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane))

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

A longer or repeated contact may lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Naphtha (petroleum)

LC50/EC50/EC50 : 1 - 10 mg/l

N-Cyclohexyl-N-ethylamine

EC50/Daphnia magna/48 h = 10 - 100 mg/l

ErC50/Desmodesmus subspicatus/72 h = 10 - 100 mg/l

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 8 of 10

Advice on disposal

Where possible recycling is preferred to disposal.
Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3295
14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 1 L / 30 kg
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

HAZCHEM: 3YE

Inland waterways transport (ADN)

14.1. UN number: UN 3295
14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 1 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 3295
14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (Naphtha (Petroleum))

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 9 of 10

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Marine pollutant: Yes

Limited quantity: 1 L / 30 kg

Excepted quantity: E2

EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): < 95 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP CEMENT SVS VULC

Revision date: 16.08.2018

Product code: 00156-0029

Page 10 of 10

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)