

Contact Sheet



Europe

 **Austria**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Belgium / Lux**
Tel: + 32 58235140
Sparex Belgium Bvba
Toevluchtweg 9
B- 8620 Nieuwpoort

 **Denmark**
Tel: + 45 647 22287
Sparex Denmark
Sparex Limited ApS
Messevej 1
9600 Aars

 **France**
Tel: +33 2987 89234
Sparex S.A.R.L.
Zae De Ty Douar
Commana 29450

 **Germany**
Tel: + 49 4282 93100
Sparex Germany
Hansestrasse 03
Sittensen 27419

 **Ireland**
Tel: +353 51 855592
Sparex (Tractor Accessories) Ltd
Grannagh
Waterford
Ireland

 **Italy**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Netherlands**
Tel: + 31 235 841 020
Sparex Holland BV
Luzernstraat 19N
2153 GM Nieuw-Vennep

 **Poland**
Tel: +48 61 816 19 37
61-168 ul. Rataje 164, Poznań

 **Portugal**
Tel: +351 261 311107
Sparex Portugal, Importação
e Comércio de Peças,Lda.
Lugar da Espera 2565-716 Runa.

 **Spain**
Tel: + 349 451 33524
Sparex Agrirepuestos,S.L. C/Jose Maria
Iparraguirre
No.15 B
01006 Vitoria-Gasteiz (Alava)

 **UK**
Tel: +44 1392 441338
Sparex Limited
Exeter Airport Devon
Exeter EX5 2LJ

North America

 **Canada**
Tel: + 905 786 277
Sparex Canada Highway
No. 2 On Newcastle L1b 119

 **USA**
Tel: + 1 330 562 8150
Sparex US
PO Box 510
Aurora, OH 44202

Africa

 **South Africa**
Cape - Tel: +27 00 21 887 3575
KZN - Tel: + 27 31 573 1240
Cape branch
35 George Blake St,
Plankenburg
Stellenbosch 7600
KZN branch
59 Marseilles crescent
Briardene
Durban 4001

Australasia

 **Australia**
Tel: + 61 298 205 777
Sparex Australia Pty Ltd
81-83 Strzelecki Avenue,
Sunshine West, VIC 3020

 **New Zealand**
Tel: + 64 9634 4121
4 Princes Street Onehunga,
Auckland 1345

Sparex Export Markets

 **Export**
Tel: +44 1392 441314
Sparex Limited
Exeter Airport
Devon Exeter EX5 2LJ

SAFETY DATA SHEET



TB300 Synthetic Topcoat Binder High Gloss

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TB300 Synthetic Topcoat Binder High Gloss
Product description : Not available.
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Uses in Coatings - Topcoat

1.3 Details of the supplier of the safety data sheet

Valspar b.v.
Zuiveringweg 89
8243 PE Lelystad
The Netherlands
tel: +31 (0)320 292200
fax: +31 (0)320 292201

e-mail address of person responsible for this SDS : msds@valspar.com

National contact

GPS Automotive Lelystad
tel: +31 (0)320 292288
fax: +31 (0)320 292201

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : Angola +01-813-248-0573
Azerbaijan +01-813-248-0573
Cambodia +01-813-248-0573
Côte d'Ivoire +01-813-248-0573
Ethiopia +01-813-248-0573
French Polynesia +01-813-248-0573
Georgia +01-813-248-0573
Ghana +01-813-248-0573
India 000-800-100-4086
Israel 1-809-315658
Kazakhstan +01-813-248-0573
Kenya +01-813-248-0573
Madagascar +01-813-248-0573
Mozambique +01-813-248-0573
Nigeria +01-813-248-0573
Philippines 1-800-1-116-0912
Sierra Leone +01-813-248-0573
Singapore +65-31585003
South Africa +27-875502286
Tanzania +01-813-248-0573
Thailand +66-21055749
Uganda +01-813-248-0573

Supplier

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Telephone number : Call: +31 (0)320 292200 (during daytime)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
Skin Irrit. 2, H315
Eye Irrit. 2, H319
STOT SE 3, H336
STOT RE 1, H372
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R10
Xn; R20/21, R48/20
R66
N; R51/53

Physical/chemical hazards : Flammable.

Human health hazards : Harmful by inhalation and in contact with skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Repeated exposure may cause skin dryness or cracking.

Environmental hazards : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : **F**lammable liquid and vapour.
Causes serious eye irritation.
Causes skin irritation.
May cause drowsiness or dizziness.
Causes damage to organs through prolonged or repeated exposure.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves. Wear eye/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Avoid release to the environment. Do not breathe vapour or spray.

Response : IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Storage : Keep cool.

SECTION 2: Hazards identification

- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazardous ingredients** : Naphtha (petroleum), hydrodesulfurized heavy xylene
- Supplemental label elements** : Contains 2-butanone oxime. May produce an allergic reaction.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

2.3 Other hazards

- Other hazards which do not result in classification** : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	w%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
Naphtha (petroleum), hydrodesulfurized heavy	REACH #: 01-2119458049-33 EC: 265-185-4 CAS: 64742-82-1 Index: 649-330-00-2	≥25 - <50	R10 Xn; R48/20, R65 R66, R67 N; R51/53	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 (inhalation) Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1] [2]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - <18	R10 Xn; R20/21 Xi; R38	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥3 - <5	F; R11 Xn; R20, R48/20, R65	Flam. Liq. 2, H225 Acute Tox. 4, H332	[1] [2]
1-methoxy-2-propanol	REACH #:	≥3 - <5	R10	STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412 Flam. Liq. 3, H226	[1] [2]

SECTION 3: Composition/information on ingredients

1,2,4-trimethylbenzene	01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3 REACH #: 01-2119472135-42 EC: 202-436-9 CAS: 95-63-6 Index: 601-043-00-3	≥1.2 - <1.9	R67 R10 Xn; R20 Xi; R36/37/38 N; R51/53	STOT SE 3, H336 Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411	[1] [2]
2-butanone oxime	EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0	≥0.3 - <1	Carc. Cat. 3; R40 Xn; R21 Xi; R41 R43 See Section 16 for the full text of the R-phrases declared above.	Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

SECTION 4: First aid measures

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-butanone oxime. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

SECTION 6: Accidental release measures

- 6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
- 6.3 Methods and material for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

- 7.1 Precautions for safe handling** : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.
- Information on fire and explosion protection**
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds (in tonnes)

Danger criteria

SECTION 7: Handling and storage

Category	Notification and MAPP threshold	Safety report threshold
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b	5000	50000
E2: Hazardous to the aquatic environment - Chronic 2	200	500
C6: Flammable (R10)	5000	50000
C9ii: Toxic for the environment	200	500

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Naphtha (petroleum), hydrodesulfurized heavy xylene	EU OEL (Europe, 2003). TWA: 575 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.
ethylbenzene	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values STEL: 442 mg/m ³ , 0 times per shift, 15 minutes. STEL: 100 ppm, 0 times per shift, 15 minutes. TWA: 221 mg/m ³ , 0 times per shift, 8 hours. TWA: 50 ppm, 0 times per shift, 8 hours.
1-methoxy-2-propanol	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values STEL: 884 mg/m ³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 442 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.
1,2,4-trimethylbenzene	80/1107/EEC (Europe). CEIL: 360 mg/m ³ CEIL: 100 ppm EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values STEL: 568 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m ³ 8 hours. TWA: 100 ppm 8 hours. 80/1107/EEC (Europe). CEIL: 20 ppm CEIL: 100 mg/m ³ EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values TWA: 100 mg/m ³ 8 hours. TWA: 20 ppm 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace

SECTION 8: Exposure controls/personal protection

atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects	
Naphtha (petroleum), hydrodesulfurized heavy	DNEL	Long term Inhalation	330 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	44 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	71 mg/m ³	Consumers	Systemic	
	DNEL	Long term Dermal	26 mg/kg bw/day	Consumers	Systemic	
	DNEL	Long term Oral	26 mg/kg bw/day	Consumers	Systemic	
	xylene	DNEL	Short term Inhalation	289 mg/m ³	Workers	Local
		DNEL	Short term Inhalation	289 mg/m ³	Workers	Systemic
		DNEL	Long term Inhalation	77 mg/m ³	Workers	Systemic
		DNEL	Long term Dermal	180 mg/kg	Workers	Systemic
		DNEL	Short term Inhalation	174 mg/m ³	Consumers	Local
DNEL		Short term Inhalation	174 mg/m ³	Consumers	Systemic	
DNEL		Long term Inhalation	14.8 mg/m ³	Consumers	Systemic	
DNEL		Long term Dermal	108 mg/kg	Consumers	Systemic	
DNEL		Long term Oral	1.6 mg/kg	Consumers	Systemic	
DNEL		Long term Inhalation	77 mg/m ³	Workers	Systemic	
ethylbenzene	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	15 mg/m ³	Consumers	Systemic	
	DNEL	Long term Oral	1.6 mg/kg bw/day	Consumers	Systemic	
	DNEL	Short term Inhalation	553.5 mg/m ³	Workers	Local	
1-methoxy-2-propanol	DNEL	Long term Inhalation	369 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	50.6 mg/kg	Workers	Systemic	
	DNEL	Long term Inhalation	43.9 mg/m ³	Consumers	Systemic	
	DNEL	Long term Dermal	18.1 mg/kg	Consumers	Systemic	
	DNEL	Long term Oral	3.3 mg/kg	Consumers	Systemic	

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
xylene	Fresh water	0.327 mg/l	-
	Marine water	0.327 mg/l	-
	Fresh water sediment	12.46 mg/kg	-
	Marine water sediment	12.46 mg/kg	-
	Soil	2.31 mg/kg	-
	Sewage Treatment Plant	6.58 mg/l	-
ethylbenzene	Fresh water	0.1 mg/l	-

SECTION 8: Exposure controls/personal protection

1-methoxy-2-propanol	Marine water	0.01 mg/l	-
	Fresh water sediment	13.7 mg/kg	-
	Marine water sediment	1.37 mg/kg	-
	Soil	2.68 mg/kg	-
	Sewage Treatment Plant	9.6 mg/l	-
	Fresh water	10 mg/l	-
	Fresh water sediment	41.6 mg/kg	-
	Marine water sediment	4.17 mg/kg	-
	Soil	2.47 mg/kg	-
	Sewage Treatment Plant	100 mg/l	-

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: chemical splash goggles and/or face shield.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 polyvinyl alcohol (PVA) ≥ 0.7 mm
< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR (≥ 0.35 mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves immediately.

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

SECTION 8: Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Cotton or cotton/synthetic overalls or coveralls are normally suitable.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: EN 405:2001 + A1:2009 organic vapour (Type A) and particulate filter FFA2P3 R D
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Not available.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : 100°C
- Flash point** : Closed cup: 30°C
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Upper/lower flammability or explosive limits** : Not available.
- Vapour pressure** : Not available.
- Vapour density** : Not available.
- Relative density** : 0.947
- Solubility(ies)** : Insoluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/ water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Explosive properties** : Not available.
- Oxidising properties** : Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-butanone oxime. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Naphtha (petroleum), hydrodesulfurized heavy	LC50 Inhalation Vapour	Rat	>10 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
xylene	LC50 Inhalation Vapour	Rat	27.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	>9.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>15000 mg/kg	-
	LD50 Oral	Rat	>3500 mg/kg	-
1-methoxy-2-propanol	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	4016 mg/kg	-
1,2,4-trimethylbenzene	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	>4.8 mg/l	4 hours
2-butanone oxime	LD50 Dermal	Rabbit	1000 to 1800 mg/kg	-
	LD50 Oral	Rat	3680 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

SECTION 11: Toxicological information

Route	ATE value
Dermal	8553.4 mg/kg
Inhalation (vapours)	57.41 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
1-methoxy-2-propanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
2-butanone oxime	Eyes - Severe irritant	Rabbit	-	100 microliters	-

Conclusion/Summary : Not available.

Sensitisation

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrodesulfurized heavy xylene	Category 3 Category 3	Not applicable. Not applicable.	Narcotic effects Respiratory tract irritation
1-methoxy-2-propanol 1,2,4-trimethylbenzene	Category 3 Category 3	Not applicable. Not applicable.	Narcotic effects Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrodesulfurized heavy xylene ethylbenzene	Category 1 Category 2 Category 2	Inhalation Not determined Not determined	Not determined Not determined hearing organs

Aspiration hazard

SECTION 11: Toxicological information

Product/ingredient name	Result
Naphtha (petroleum), hydrodesulfurized heavy xylene ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
Naphtha (petroleum), hydrodesulfurized heavy	EC50 >100 mg/l	Daphnia	48 hours
xylene	LC50 >100 mg/l Acute EC50 1 to 10 mg/l Acute EC50 1 to 10 mg/l Acute LC50 1 to 10 mg/l	Fish Algae Daphnia - Daphnia magna Fish	96 hours 72 hours 48 hours 96 hours
ethylbenzene	Acute EC50 >1.8 mg/l Acute LC50 >10 mg/l	Daphnia - Daphnia magna Fish - Pimephales promelas	48 hours 96 hours
1-methoxy-2-propanol	Acute EC50 23300 mg/l Acute LC50 6812 mg/l	Daphnia - Daphnia magna Fish - Leuciscus idus	48 hours 96 hours
1,2,4-trimethylbenzene	Acute EC50 1 to 10 mg/l	Fish	96 hours
2-butanone oxime	EC50 6.1 to 11.6 mg/l LC50 750 mg/l LC50 >100 mg/l	Algae Daphnia Fish	72 hours 48 hours 96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1-methoxy-2-propanol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	8.1 to 25.9	low
ethylbenzene	3.6	-	low
1-methoxy-2-propanol	<1	-	low
1,2,4-trimethylbenzene	3.63	243	low
2-butanone oxime	0.63	2.5 to 5.8	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

SECTION 12: Ecological information

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Paint Guidelines	15 01 10* packaging containing residues of or contaminated by dangerous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINTPAINT	PAINT. Marine pollutant (Naphtha (petroleum), hydrodesulfurized heavy, 1,2, 4-trimethylbenzene)	Paint

SECTION 14: Transport information

14.3 Transport hazard class(es)	3 	3 	3 	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	No.
Additional information	<p>The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.</p> <p>Hazard identification number 30</p> <p>Limited quantity LQ7</p> <p>Special provisions 163 640E 650</p> <p>Tunnel code (D/E)</p>	<p>The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.</p> <p>Special provisions 163 640E 650</p>	<p>The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.</p> <p>Emergency schedules (EmS) F-E, _S-E_</p> <p>Special provisions 163, 223, 955</p>	<p>The environmentally hazardous substance mark may appear if required by other transportation regulations.</p> <p>Passenger and Cargo Aircraft Quantity limitation: 60 L Packaging instructions: 309</p> <p>Cargo Aircraft Only Quantity limitation: 220 L Packaging instructions: 310</p> <p>Limited Quantities - Passenger Aircraft Quantity limitation: 10 L Packaging instructions: Y309</p> <p>Special provisions A3, A72</p>

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

SECTION 15: Regulatory information

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

Europe inventory : All components are listed or exempted.

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
2-butanone oxime	Carc. 2, H351	-	-	-

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b E2: Hazardous to the aquatic environment - Chronic 2 C6: Flammable (R10) C9ii: Toxic for the environment

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

National inventory

- Australia** : All components are listed or exempted.
- Canada** : All components are listed or exempted.
- China** : Not determined.
- Japan** : Not determined.
- Malaysia** : Not determined.
- New Zealand** : All components are listed or exempted.
- Philippines** : Not determined.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : Not determined.
- United States** : All components are listed or exempted.

TB300 Synthetic Topcoat Binder High Gloss

SECTION 15: Regulatory information

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

CEPE code : 1

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 STOT RE 1, H372 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements : H225 H226 H304 H312 H312 (dermal) H315 H317 H318 H319 H332 (inhalation) H335 H336 H351 H372 H372 (inhalation) H373 H373 (hearing organs) H411 H412	Highly flammable liquid and vapour. Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. Causes damage to organs through prolonged or repeated exposure if inhaled. May cause damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure. (hearing organs) Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Full text of classifications [CLP/GHS] : Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Chronic 2, H411 Aquatic Chronic 3, H412 Asp. Tox. 1, H304 Carc. 2, H351 EUH066 Eye Dam. 1, H318 Eye Irrit. 2, H319 Flam. Liq. 2, H225	ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 LONG-TERM AQUATIC HAZARD - Category 2 LONG-TERM AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 2 Repeated exposure may cause skin dryness or cracking. SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 16: Other information

Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1, H317	SKIN SENSITIZATION - Category 1
STOT RE 1, H372	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
STOT RE 1, H372 (inhalation)	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (inhalation) - Category 1
STOT RE 2, H373	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT RE 2, H373 (hearing organs)	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2
STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Full text of abbreviated R phrases

- : R11- Highly flammable.
- R10- Flammable.
- R40- Limited evidence of a carcinogenic effect.
- R20- Harmful by inhalation.
- R21- Harmful in contact with skin.
- R20/21- Harmful by inhalation and in contact with skin.
- R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R65- Harmful: may cause lung damage if swallowed.
- R41- Risk of serious damage to eyes.
- R38- Irritating to skin.
- R36/37/38- Irritating to eyes, respiratory system and skin.
- R43- May cause sensitisation by skin contact.
- R66- Repeated exposure may cause skin dryness or cracking.
- R67- Vapours may cause drowsiness and dizziness.
- R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of classifications [DSD/DPD]

- : F - Highly flammable
- Carc. Cat. 3 - Carcinogen category 3
- Xn - Harmful
- Xi - Irritant
- N - Dangerous for the environment

- Date of printing** : 24/03/2016
- Date of issue/ Date of revision** : 24/03/2016
- Date of previous issue** : 23/09/2015
- Version** : 1.3

Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.