SPX/Q903 - Sparex Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 26/04/2023 Revision date: 12/06/2023 Supersedes version of: 26/04/2023 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Product name	:	SPX/Q903 - Sparex Hardener
UFI	:	SX3Q-52WK-400U-2VN8
Product code	:	21195
Type of product	:	Reaction product
Product group	:	Blend
Other means of identification	:	SPX/Q903/C

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	:	Professional use
Use of the substance/mixture	:	Part of a 2 Pack coating system.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier
Sparex Ltd
Exeter Airport
Exeter – Devon EX5 2LJ
United Kingdom
T +44 (0)1392 266592
msds.qc@sparex.com

Distributor
Sparex Agrirepuestos,S.L.
C/Jose Maria Iparraguirre No.15 B
01006 Vitoria-Gasteiz (Alava)
Espana
T +349 451 33524
msds.qc@sparex.com

Distributor
Sparex Germany
Hansestrasse 03
Sittensen 27419
Deutschland
T +49 4282 93100
msds.qc@sparex.com

Distributor
Sparex Limited
c/o AGCO SAS
c/o AGCO SAS ZAC DE LA FONTAINE DES SAINTS
RUE ANDRE CITROEN (BAT. B) 57365 ENNERY
FRANCE
T +44 (0)1392 266592
msds.qc@sparex.com

Distributor
Sparex Portugal-Importação
e Comercio de Peças Lda Lugar da Espera
2565-716 Runa
T +351 261 311107
msds.qc@sparex.com

Distributor
Sparex (Tractor Accessories) Ltd
Grannagh – Waterford
Ireland
T Tel: +353 51 855592
msds.qc@sparex.com

Distributor
Sparex Denmark
Sparex Ltd ApS Messevej 1
9600 Aars
Denmark
T +45 647 22287
msds.qc@sparex.com

Distributor
Sparex Holland BV
Luzernestraat 19N 2153 GM Nieuw-Vennep
Nederland
T 31 235 841 020
msds.qc@sparex.com

Distributor
Sparex Poland
61-169 ul. Rataje 164
Poznan
Polska
T +48 61 816 19 37
msds.qc@sparex.com

Distributor
Sparex S.A.R.L
Zae De Ty Douar
Commana – 29450
France
T +33 2987 89234
msds.qc@sparex.com

1.4. Emergency telephone number

Emergency number	:	GBK GmbH Global Regulatory Compliance Tel.: +49 (6132) 84463. Infotrac-ID: 114576

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Acute toxicity (inhal.), Category 4	H332
Skin sensitisation, Category 1	H317
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS02 GHS07

Signal word (CLP)	:	Warning
Contains	:	BUTYL ACETATE -norm; ISOPHORONE DI-ISOCYANATE; 2-METHOXY-1-METHYLETHYL ACETATE; HYDROCARBONS, C9, AROMATICS; Xylene isomer mixture(with up to 20% Ethylbenzene); Isophorondiisocyanate Homopolymer
Hazard statements (CLP)	:	H226 - Flammable liquid and vapour. H317 - May cause an allergic skin reaction. H332 - Harmful if inhaled. H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	:	P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P501 - Dispose of contents/container to national regulations.
EUH-statements	:	EUH204 - Contains isocyanates. May produce an allergic reaction.
Extra phrases	:	For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isophorondiisocyanate Homopolymer	CAS-No.: 53880-05-0	≥ 30 – < 50	Skin Sens. 1B, H317 STOT SE 3, H335
BUTYL ACETATE -norm substance with national workplace exposure limit(s) (GB)	CAS-No.: 123-86-4 EC-No.: 204-658-1 REACH-no: 01-2119485493-29	≥ 10 – < 30	Flam. Liq. 3, H226 STOT SE 3, H336
2-METHOXY-1-METHYLETHYL ACETATE substance with national workplace exposure limit(s) (GB)	CAS-No.: 108-65-6 EC-No.: 203-603-9 REACH-no: 01-2119475791-29	≥ 5 – < 10	Flam. Liq. 3, H226 STOT SE 3, H336
Xylene isomer mixture(with up to 20% Ethylbenzene) substance with national workplace exposure limit(s) (GB)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 REACH-no: 01-2119488216-32	≥ 5 – < 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
HYDROCARBONS, C9, AROMATICS substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	≥ 5 – < 10	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ISOPHORONE DI-ISOCYANATE	CAS-No.: 4098-71-9 EC-No.: 223-861-6	< 1	Acute Tox. 1 (Inhalation), H330 (ATE=0.005 mg/l/4h) Acute Tox. 3 (Inhalation:dust,mist), H331 (ATE=0.005 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Seek medical attention immediately.

First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. Give oxygen or artificial respiration if necessary. Get medical advice/attention. If unconscious place in recovery position and seek medical advice.

First-aid measures after skin contact : Get medical advice/attention. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion : Rinse mouth out with water. Drink plenty of water. Do NOT induce vomiting. Get medical advice/attention. Go into open air and ventilate suspected area.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause headache, nausea and irritation of respiratory tract.
Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2).
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Vapours may cause fire/explosion if source of ignition is present.
Explosion hazard : Explosion risk in case of fire.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire : Avoid breathing (dust, vapor, mist, gas). Evacuate area. Cool down the containers exposed to heat with a water spray.
Firefighting instructions : Prevent fire fighting water from entering the environment.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.
Other information : On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : See section 8 of the SDS for more information on personal protective equipment. Do not breathe vapours. Ventilate spillage area.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent liquid from entering sewers, watercourses, underground or low areas. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautions for safe handling	:	Provide adequate ventilation to minimize dust and/or vapour concentrations. Use only non-sparking tools. Wear personal protective equipment. Do not breathe vapours.
Hygiene measures	:	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Proper grounding procedures to avoid static electricity should be followed. Store in a well-ventilated place. Keep container tightly closed. Use only non-sparking tools. Ensure adequate ventilation, especially in confined areas.
Storage conditions	:	Store in original container.
Incompatible products	:	Oxidizing agent.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

BUTYL ACETATE -norm (123-86-4)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	724 mg/m³
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	996 mg/m³
WEL STEL (OEL STEL) [ppm]	200 ppm

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	50 mg/m³ GB EH40
WEL STEL (OEL STEL)	100 mg/m³ GB EH40

HYDROCARBONS, C9, AROMATICS (64742-95-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	100 mg/m³
IOEL TWA [ppm]	25 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	100 mg/m³ (8 hour)
WEL TWA (OEL TWA) [2]	25 ppm (8 hour)

Xylene isomer mixture(with up to 20% Ethylbenzene) (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	220 mg/m³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	441 mg/m³
WEL STEL (OEL STEL) [ppm]	100 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Provide local exhaust or general room ventilation. Personal, workplace, environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Wear personal protective clothing (see chapter 8).

8.2.2. Personal protection equipment

Personal protective equipment:
Wear respiratory protection.

Personal protective equipment symbol(s):

8.2.2.1. Eye and face protection

Eye protection:
Safety glasses (EN 166)

8.2.2.2. Skin protection

Hand protection:
Protective gloves against chemicals (EN 374). As a general principal, exposure should be managed by means other than the provision of protective gloves. Permeation time: minimum >480min long term exposure; material / thickness [mm]:

Other skin protection

Materials for protective clothing:
Use protective clothing. protective footwear

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Combined respiratory protective device, for filtering gas and particles, with a specific canister

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

Consumer exposure controls:
Do not exceed the occupational exposure limits (OEL).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Colourless to pale yellow.
Appearance	:	Liquid.
Odour	:	Not available
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not available
Explosive limits	:	Not available
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	~ 40°C Closed cup.
Auto-ignition temperature	:	420 °C
Decomposition temperature	:	Not available
pH	:	Not available.
Viscosity, kinematic	:	> 20.5 mm²/s
Viscosity, dynamic	:	1500 mPa·s @ 25°C
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	Not available
Relative density	:	1.08 @20°C
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

SPX/Q903 - Sparex Hardener	
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h

Isophorondiisocyanate Homopolymer (53880-05-0)	
LD50 oral rat	14100 mg/kg
LC50 Inhalation - Rat	6 mg/l

Skin corrosion/irritation : Not classified
pH: Not available.

HYDROCARBONS, C9, AROMATICS (64742-95-6)	
pH	Not available.

Serious eye damage/irritation : Not classified
pH: Not available.

HYDROCARBONS, C9, AROMATICS (64742-95-6)	
pH	Not available.

Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

BUTYL ACETATE -norm (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

ISOPHORONE DI-ISOCYANATE (4098-71-9)	
STOT-single exposure	May cause respiratory irritation.

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
STOT-single exposure	May cause drowsiness or dizziness.

HYDROCARBONS, C9, AROMATICS (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

Xylene isomer mixture(with up to 20% Ethylbenzene) (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.

Isophorondiisocyanate Homopolymer (53880-05-0)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

Xylene isomer mixture(with up to 20% Ethylbenzene) (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

SPX/Q903 - Sparex Hardener	
Viscosity, kinematic	> 20.5 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

Not rapidly degradable

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Completely empty the packaging prior to decontamination.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment.

European List of Waste (LoW) code : 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
15 01 02 - plastic packaging
15 01 04 - metallic packaging

HP Code : HP3 - “Flammable:”
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
HP5 - “Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:” waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
HP6 - “Acute Toxicity:” waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
HP13 - “Sensitising:” waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.
HP14 - “Ecotoxic:” waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1866	UN 1866	UN 1866	UN 1866	UN 1866
14.2. UN proper shipping name				
RESIN SOLUTION	RESIN SOLUTION	Resin solution	RESIN SOLUTION	RESIN SOLUTION
Transport document description				
UN 1866 RESIN SOLUTION, 3, III, (D/E)	UN 1866 RESIN SOLUTION, 3, III	UN 1866 Resin solution, 3, III	UN 1866 RESIN SOLUTION, 3, III	UN 1866 RESIN SOLUTION, 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1

Limited quantities (ADR) : 5l

Excepted quantities (ADR)	:	E1
Packing instructions (ADR)	:	P001, IBC03, LP01, R001
Special packing provisions (ADR)	:	PP1
Mixed packing provisions (ADR)	:	MP19
Portable tank and bulk container instructions (ADR)	:	T2
Portable tank and bulk container special provisions (ADR)	:	TP1
Tank code (ADR)	:	LGBF
Vehicle for tank carriage	:	FL
Transport category (ADR)	:	3
Special provisions for carriage - Packages (ADR)	:	V12
Special provisions for carriage - Operation (ADR)	:	S2
Hazard identification number (Kemler No.)	:	30
Orange plates	:	
Tunnel restriction code (ADR)	:	D/E
EAC code	:	•3Y

Transport by sea

Special provisions (IMDG)	:	223, 955
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	P001, LP01
Special packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T2
Tank special provisions (IMDG)	:	TP1
EmS-No. (Fire)	:	F-E
EmS-No. (Spillage)	:	S-E
Stowage category (IMDG)	:	A
Properties and observations (IMDG)	:	Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y344
PCA limited quantity max net quantity (IATA)	:	10L
PCA packing instructions (IATA)	:	355
PCA max net quantity (IATA)	:	60L
CAO packing instructions (IATA)	:	366
CAO max net quantity (IATA)	:	220L
Special provisions (IATA)	:	A3
ERG code (IATA)	:	3L

Inland waterway transport

Classification code (ADN)	:	F1
Limited quantities (ADN)	:	5 L
Excepted quantities (ADN)	:	E1
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01
Number of blue cones/lights (ADN)	:	0

Rail transport

Classification code (RID)	:	F1
Limited quantities (RID)	:	5L
Excepted quantities (RID)	:	E1
Packing instructions (RID)	:	P001, IBC03, LP01, R001
Special packing provisions (RID)	:	PP1
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T2

Portable tank and bulk container special provisions (RID)	:	TP1
Tank codes for RID tanks (RID)	:	LGBF
Transport category (RID)	:	3
Special provisions for carriage – Packages (RID)	:	W12
Colis express (express parcels) (RID)	:	CE4
Hazard identification number (RID)	:	30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 and all its amendments and modifications. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 and all its amendments and modifications.

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail

Abbreviations and acronyms:	
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative
CAS-No.	Chemical Abstract Service number

Full text of H- and EUH-statements:	
Acute Tox. 1 (Inhalation)	Acute toxicity (inhal.), Category 1
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH204	Contains isocyanates. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

Full text of H- and EUH-statements:	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.