Product Name: UNI-B CJ-4/SN 15W40

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name TRU-BLU OIL AUSTRALIA PTY LTD

Address 6 Dunlop Court , Bayswater , Victoria, AUSTRALIA, 3153

 Telephone
 (03) 9720 4400

 Fax
 (03) 9720 5821

 Emergency
 0412 609 722

Email technical@trubluoil.com.au Web Site http://www.trubluoil.com.au/

Synonym(s) CJ-4/SN 15W40

Use(s) ENGINE OIL LUBRICANT SDS Date 12th December 2019

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG

GHS Classification: Not a hazardous substance or mixture.

Flammable Liquid Category 4 Carcinogenetic Category 1B

GHS Pictogram:



Signal Word: Danger

Hazard Statements: H350: May Cause Cancer.

UN No. None Allocated
DG Class None Allocated
Subsidiary Risk(s) None Allocated
Packing Group None Allocated
Hazchem Code None Allocated

Last Edited: 07/07/2020

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content		
No Reportable Hazardous Substance	Not Available	Not Available	>75%		
Additives	Not Available	Not Available	<18%		
Highly Refined Mineral	Not Available	64842-65-0	<5%		
Phosohorodithioic	Not Available	113709-15-3	<2%		
No Reportable Hazardous Substance(s) or Complex Substance(s)					

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue

flushing until advised to stop by a Poisons Information Centre, a doctor, or for at

least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not

breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and

hair with running water. Continue flushing with water until advised to stop by a

Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a

doctor (at once). If swallowed, do not induce vomiting.

Advice to Doctor Treat symptomatically.

First Aid Facilities Eye wash facilities and safety shower should be available.

5. FIRE FIGHTING MEASURES

Flammability Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated

to decomposition.

Fire and Explosion Evacuate area and contact emergency services. Toxic gases may be evolved in a

fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

Extinguishing Dry agent, carbon dioxide or foam. Prevent contamination of drains or

waterways.

Hazchem Code None Allocated

6. ACCIDENTAL RELEASE MESAURES

Spillage Use personal protective equipment.

Clear area of all unprotected personnel.

Ventilate area where possible.

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

7. STORAGE AND HANDLING

Storage Store in a cool, dry, well ventilated area, removed from oxidising agents, acids,

alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire

protection systems. Store as a Class C4 Combustible Liquid (AS1940).

Handling Before use carefully read the product label. Use of safe work practices are

recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and

smoking in contaminated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Stds

Ingredient	Reference	T	WA	ST	EL
Oil mist, refined oil	SWA (AUS)		5 mg/m3		

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists,

mechanical extraction ventilation is recommended. Maintain vapour levels below

the recommended exposure standard.

PPE Wear splash-proof goggles and rubber or PVC gloves. When using large quantities

or where heavy contamination is likely, wear: coveralls. Where an inhalation risk

exists, wear: a Type A (Organic vapour) respirator.

With prolonged use, wear: viton (R) or nitrile gloves and coveralls.

www.trubluoil.com.au Page 3 Last Edited: 07/07/2020

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	AMBER YELLOW LIQUID	Solubility (water)	INSOLUBLE
Odour	CHARACTERISTIC ODOUR	Specific Gravity	0.872
рН	NOT RELEVANT	% Volatiles	NOT AVAILABLE
Vapour Pressure	NOT AVAILABLE	Flammability	CLASS C4 COMBUSTIBLE
Vapour Density	NOT AVAILABLE	Flash Point	> 210°C
Boiling Point	NOT AVAILABLE	Upper Explosion Limit	NOT AVAILABLE
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE		
Viscosity	15.1 cSt @ 100°C		

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to Avoid Avoid heat, sparks, open flames and other ignition sources.

Material to Avoid Incompatible with oxidising agents (eg. hypochlorites), acids (eg.

nitric acid), alkalis (eg. hydroxides), heat and ignition sources.

Hazardous Decomposition Products May evolve toxic gases (carbon oxides, hydrocarbons) when

heated to decomposition.

Hazardous Reactions Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Low toxicity. Use safe work practices to avoid eye or skin contact

and inhalation. The mineral oil contained within this product is

highly refined and therefore is not classifiable as to its

carcinogenicity in humans (IARC Group 3).

Eye Low to moderate irritant. Contact may result in irritation,

lacrimation, pain and redness.

Inhalation Low irritant. Over exposure may result in irritation of the nose

and throat, with coughing.

Skin Low irritant. Prolonged or repeated contact may result in mild

irritation, rash and dermatitis.

Ingestion Low toxicity. Ingestion of large quantities may result in nausea,

vomiting, abdominal pain, diarrhoea, and drowsiness. Aspiration may result in chemical pneumonitis and pulmonary oedema.

Toxicity Data No LD50 data available for this product.

12. ECOLOGICAL INFORMATION

Environment Mineral oils biodegrade slowly and should not be released to waterways

or soil. They can float on water, restricting oxygen exchange with possible

asphyxiation of aquatic life.

Ecotoxicity Not classified as dangerous to the aquatic environment.

Persistence / Degradability Expected to be inherently biodegradable.

Mobility Low solubility and is expected to migrate from water to the land.

Expected to partition to sediment and wastewater solids.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Reuse where possible or return to manufacturer/supplier. May be recycled.

Do not release to drains or waterways.

Contact the manufacturer for additional information.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping NameNone AllocatedDG ClassNone AllocatedUN No.None AllocatedHazchem CodeNone AllocatedPacking GroupNone AllocatedSubsidiary Risk(s)None Allocated

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the

criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

MINERAL OILS - SOLVENT REFINED; Animal experiments and human experience have not shown cancer risks when handling solvent refined mineral oils, unlike non refined mineral oils. CLEANING MINERAL OIL

CONTAMINATED CLOTHING; Cleaners are advised that when cleaning oil contaminated clothing it is essential that freshly distilled solvent is used for each batch, including final rinse, as even filtered solvent will leave oil residues.

MINERAL OILS - USED; Used mineral oils in engine crankcases and other high temperature/high stress environments may contain potentially harmful residues, some of which have been shown to cause irreversible skin effects, including cancer. Prolonged and repeated inhalation of mists associated with used mineral oils may result in pulmonary fibrosis.

MINERAL OILS - INJECTION; Where high pressure applications are used the risk of accidental injection under the skin exists and may result in an extremely painful and serious injury requiring immediate medical attention. Depending on the pressure used, mineral oils may be injected a considerable distance below the skin and may cause permanent tissue damage. SEEK IMMEDIATE MEDICAL ATTENTION. EXERCISE EXTREME CARE WHEN USING HIGH PRESSURE EQUIPMENT.

Tru-Blu Oil Australia 6 Dunlop Court Bayswater Victoria 3153. Australia Phone: (03) 9720 4400

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists.

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indice(s).

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer.

mg/m3 - Milligrams per Cubic Metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia. TWA - Time Weighted Average.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

This document has been compiled by Tru Blu Oil, the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While Tru Blu Oil has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, Tru Blu Oil accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

SDS Date: 7th July 2020 End of Report